


Key Features


10-POINT MULTI-TOUCH | POWERFUL QUAD CORE PROCESSOR |
OPTIONAL AUTOMATIC HAND SANITIZING DISPENSER | OPTIONAL
CONTENT MANAGEMENT SOFTWARE | "
EQUIPPED WITH WI-FI, BLUETOOTH, AND RJ45

Product Description

The ViewSonic® EP2410T-B1 is a Health Flex Hand Sanitizing Station bundled with a 24" touch display, media player, and hand sanitizer dispenser holder. With a sleek and slim design, and optional touchless dispenser for hands-free sanitizing, the EP2410T-B1 makes displaying health notices, business information, and promotions easier than ever. Featuring Full HD 1080p resolution, 178°/178° wide-angle viewing, 250-nit brightness, 1,000:1 contrast ratio, and dual stereo speakers, the EP2410T-B1 delivers customized multimedia messaging with vivid clarity. Photo and video files can be played back using the external Octa-core media player and 16GB of internal memory, or you can add your own media player using the convenient media player cradle inside the lockable security door. Highlight your commitment to your customers' health with the ViewSonic Health Flex Hand Sanitizing Station bundle.



24"
DISPLAY



1920 x 1080
RESOLUTION



250 cd/m2
BRIGHTNESS

16/7

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Display Size (in.):	24
Viewable Area (in.):	23.6
Resolution:	1920 x 1080
Light Source:	LED
Static Contrast Ratio:	3,000:1
Brightness:	250 cd/m2
Colors:	16.7M
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30,000
Response Time (Typical GTG):	16ms
Panel Surface:	Anti-glare, hard-coating (3H)
Panel Type:	IPS
Operation Rating:	16/7

Audio:

Internal Speakers:	2.5W (x2)
--------------------	-----------

Connector:

3.5mm Audio Out(1), 3.5mm Mic In(1), Ethernet LAN (RJ45)(1), HDMI 1.4 In(1), HDMI 1.4 Out(1), USB 2.0 Type A(4), USB 2.0 Type B(1), SD Card Slot(1), DC Jack (12V/4A)(1)

Embedded Player:

Media Player Type:	Yes
--------------------	-----

Power:

Voltage:	AC 100-240V (universal), 50-60Hz
Consumption (max):	40W
Consumption (typical):	16W
Stand-by:	<2W

Operating Conditions:

Temperature:	32~95° F (0 - 35° C)
Humidity (non-condensing):	20-90%

Specs Video Signal:

Frequency Horizontal:	15~90kHz
Frequency Vertical:	24~75Hz

Weight (imperial):

Gross (lbs):	66.7
Net (lbs):	54.4

Weight (metric):

Gross (kg):	30.3
Net (kg):	24.7

Dimensions (imperial) (WxHxD):

Packaging (in.):	65.0 x 20.0 x 20.0
Physical (in.):	60.0 x 16.0 x 16.0

Dimensions (metric) (WxHxD):

Packaging (mm):	1651.0 x 508.0 x 508.0
Physical (mm):	1524.0 x 406.4 x 406.4

General:

Regulations: cTUVus, FCC-B(including ICES003), FCC-ID, CA IC
PACKAGE CONTENTS: STND-059 x 1, VSD243 x 1
Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.
Warranty: One-year limited warranty on parts and labor