

# i3TOUCH X-ONE

Product specs 75"

## Work faster



Take advantage of the advanced Octa-core Android engine because the more powerful and updated your processor, the faster your display can complete its tasks. By getting a more powerful processor, it can help you work faster.

## Multi-function button



Define your favorite actions on a hardware button. You can set it to freeze the image, take a screenshot, switch to your preferred video input source and more.

## i3STUDIO



Our interactive displays are pre-installed with i3STUDIO. i3STUDIO delivers everything you need to accomplish your best lesson, pitch, presentation or brainstorming session. Leave the room dazzled.

## Just one cable



Use the i3TOUCH display's speakers and camera by connecting your laptop to the screen with a USB-C cable. There are even two USB-C inputs. One for audio, video, power and touch, and one for audio, video and touch.



## Room filling audio



The advanced audio system pumps out loud and full-bodied sound that is capable of filling a whole room. It handles lows, mids, and highs with competence, thanks to the integrated subwoofer. Just enjoy the premium audio during your presentation or videoconference.

## Multitasking



Supports split-screen mode allowing you to use two apps at the same time on your i3TOUCH X-ONE.

## Enhanced clarity



Optical Bonding provides many benefits including, enhanced clarity and viewability, ruggedization, improved heat dissipation and the most accurate touch experience.

## Reduced eye fatigue



With DC Dimming mode, a blue light filter, and an anti-glare coating, the i3TOUCH X-ONE offers an anti-in-class viewing experience that tremendously reduces eye fatigue. Certified by TÜV Rheinland.

## DISPLAY PROPERTIES

65"

75"

86"

Model Name	i3TOUCH X-ONE 65	i3TOUCH X-ONE 75	i3TOUCH X-ONE 86
Product series	i3TOUCH X-ONE Series - Interactive Digital Whiteboard Displays		
Product ID	10010312	10010313	10010314

## DISPLAY SPECIFICATIONS

Display technology	Liquid Crystal Display (LCD) with Direct-LED backlight		
Panel Type	IPS-ADS		
Display aspect ratio	16:9		
Display native resolution	3840 x 2160 pixels - 4K Ultra High Definition		
Brightness (typical)	400 cd/m <sup>2</sup>		
Brightness (maximum)	450 cd/m <sup>2</sup>		
Contrast ratio (typical)	1200:1		
Dynamic contrast ratio	4000:1		
Viewing angle	178° / 178°		
Colour depth	1.07 billion colors (10 bit)		
Response time (typ.)	8 ms		
Refresh rate	60 Hz (@ UHD)		
Pixel pitch	0.372 x 0.372 mm	0.429 x 0.429 mm	0.4935 x 0.4935 mm
Glass	2.7 mm Hardened Anti-Reflection Safety Glass (MOHS 7)		
Panel MTBF	50,000 hours		
Panel-Glass Bonding	Optical bonding (no air gap)		
Sensors	Ambient Light Sensor, Motion Sensor		
Supported Orientation	Landscape		

CONNECTIVITY

Digital audio-video input	2x HDMI 2.0, incl CEC, ARC
	1x DisplayPort 1.2
Digital audio-video-data ports	1x USB 3.0 Type C, incl PowerDelivery 65W charging, Alternate Mode DP, and USB data
	1x USB 3.0 Type C, incl Alternate Mode DP, and USB data
Digital audio-video output	1x HDMI 2.0
Digital audio output	1x S/PDIF Optical
USB Data ports	2x USB 3.0 Type A (switching via touch input)
	1x USB 3.0 Type A (Android)
Integrated OPS slot	OPS-PC slot (JAE TX24 connector) UHD
Control input	COM DE-9 (RS-232 standard)
Network connectivity	2x LAN: RJ-45 connector (1000 Mbit/sec)
	Wi-Fi 5 = 802.11ac
Analog audio output	1x Audio Jack 3.5 mm TRS

OPERATIONAL SPECIFICATIONS

Operating System	Android 11
Architecture	CPU : ARM A73 (4 cores) + A53 (4 cores)
	Clock speed : 2.8 GHz
	Cores : 8
	GPU : Mali G52
	RAM : 8 GB DDR4
	ROM : 32 GB
Interactive touch	Technology: V-Sense Infrared Touch recognition
	Resolution : 32768 x 32768
	Accuracy : 1 mm
	Response time : < 10 ms
	Connection : 3x USB-B 3.0
	Connection protocol: HID (Human Interface Device)
	Touch Points: 40 simultaneous multi-touch points
Maximum Daily Operating hours	18 hours / day
Loudspeakers	2x 20 Watt
Subwoofer	15 Watt

PHYSICAL PROPERTIES

Product Dimensions	59.67" x 35.63" x 4.53"	68.50" x 40.55" x 4.53"	78.20" x 46.02" x 4.53"
Packaging Dimensions	64.57" x 8.70" x 40.79"	73.20" x 8.94" x 45.40"	83.43" x 8.94" x 50.00"
VESA Mounting Pattern	600x400	800x400	800x400
Net Product Weight	88.2 lbs	112.4 lbs	143.3 lbs
Gross Packaged Weigth	112.4 lbs	147.7 lbs	180.8 lbs

WARRANTY

Standard Warranty	5 years
Extended Warranty	for education entities: 8 years (via registration) for corporate entities: 8 years (available for purchase)

## ACCESSOIRES

Included	User Manual
	EU Power Cable 14.8 ft, US Power Cable 5.9 ft, UK Power Cable 5.9 ft
	USB-C 3.1 Cable 9.8 ft
	HDMI Cable 9.8 ft
	USB-Touch Cable 9.8 ft
	Remote control
	2 x passive stylus
	Wall Mount

## REGULATORY INFORMATION

Type Approval	CE, FCC
---------------	---------

## SOFTWARE FEATURES

User Interface	i3STUDIO (Fully Customizable Launcher)
Whiteboarding Software	i3WHITEBOARD
Annotation Software	i3WHITEBOARD
Screencasting Software	i3ALLSYNC Wireless Presenting
Operating System	Android 11
Update Support	OTA (Over-the-Air)
Web Browser	Chromium
Support	Apple Airplay & Google Chromecast
Conferencing	Zoom, WebEx, or browser-based
App Store	i3STORE (ability to download and install apps)
Remote Support	Ability to offer remote assistance (requires i3RDM license)

## ELECTRICAL PROPERTIES

Input Power	100 ~ 240 Volt – 50/60 Hz		
Power Consumption	133 Watt	150 Watt	168 Watt
Energy Saving Features	Auto-brightness adjustment by Ambient Light Sensor		

## ENVIRONMENTAL CONDITIONS

Operating Temperature	32 °F to 104 °F
Operating Humidity	10% to 90% RH non-condensing
Operating Maximum Altitude	16404.2 ft
Storage Temperature	-4 °F to 104 °F
Storage Humidity	10% to 90% RH non-condensing

