

Key Features

- 100Hz refresh rate for smooth gameplay
- 1ms (MPRT) response time for precision
- AMD FreeSync[™] prevents screen tearing
- Full HD resolution for high detail



Product **Description**

The ViewSonic VX2416 features a crisp Full HD display paired with a hyper-responsive 100Hz refresh rate for smooth gaming. The 100Hz refresh rate loads more frames for sleek gameplay with less lag. A 1ms response time ensures your reactions are as fast as the game, helping you to claim more victories. AMD FreeSync™ virtually eliminates screen tearing and stuttering for the smoothest gaming experience possible.

Visit Us

www.viewsonic.com

DISPLAY		INPUT SIGNAL	
Display Size (in.):	24	Frequency Horizontal:	24 ~ 115KHz
Viewable Area (in.):	23.8	Frequency Vertical:	48 ~ 100Hz
Panel Type:	IPS Technology	VIDEO INPUT	
Resolution:	1920 x 1080	Digital Sync:	TMDS - HDMI (v1.4), PCI-E -
Resolution Type:	FHD (Full HD)	ERGONOMICS	DisplayPort (v1.2)
Static Contrast Ratio:	1,000:1 (typ)	Tilt (Forward/Back):	-5° / 20°
Dynamic Contrast Ratio:	80M:1	WEIGHT (IMPERIAL)	0 / 20
Light Source:	LED	Net (lbs):	7.7
Brightness:	250 cd/m² (typ)	Net Without Stand (lbs):	7.1
Colors:	16.7M	Gross (lbs):	10.8
Color Space Support:	8 bit (6 bit + Hi-FRC)	WEIGHT (METRIC)	
Aspect Ratio:	16:9	Net (kg):	3.5
Response Time (MPRT):	1ms	Net Without Stand (kg):	3.2
Viewing Angles:	178º horizontal, 178º vertical	Gross (kg):	4.9
Backlight Life (Hours):	30000 Hrs (Min)	DIMENSIONS (IMPERIAL) (W	/XHXD)
Curvature:	Flat	Packaging (in.):	23.7 x 15.7 x 5.5
Refresh Rate (Hz):	100	Physical (in.):	21.2 x 15.4 x 8.6
Variable Refresh Rate	Face 2010	Physical Without Stand (in.):	21.2 x 12.8 x 1.7
Technology:	FreeSync	DIMENSIONS (METRIC) (WX	
Blue Light Filter:	Yes	Packaging (mm):	602 x 398 x 140
Flicker-Free:	Yes	Physical (mm):	540 x 391 x 218
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)	Physical Without Stand (mm):	540 x 325 x 43
Pixel Size:	0.275 mm (H) x 0.275 mm (V)	GENERAL	
Surface Treatment:	Anti-Glare, Hard Coating (3H)		cTUVus, FCC-B, ICES003, Energy
	Anti-Glare, Hard Coating (311)	Regulations:	Star, EPEAT, CEC, TUV S-Mark, NOM, Mexico Energy, CB, RoHS,
PC Resolution (max):	1920x1080		WEEE, BSMI
Mac® Resolution (max):	1920x1080	PACKAGE CONTENTS:	VX2416 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, Quick Start Guide x1
	Windows 10/11 certified; macOS		
PC Operating System:	tested	Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Mac® Resolution (min): CONNECTOR	1920x1080	Warranty:	*Warranty offered may differ from
3.5mm Audio Out:	1		market to market
HDMI 1.4:	1	Country Of Origin:	70
DisplayPort:	1	Power Management:	Energy Star standards, EPEAT
Power in: AUDIO	3-pin Socket (IEC C14 / CEE22)		
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	14W		
Eco Mode (optimized):	16W		
Consumption (typical):	18W		
Consumption (typical).	22W		
,	AC 100-240V		
Voltage: Stand-by:	0.5W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE Kensington Lock Slot:	1		
CONTROLS	I		
	Key 1 (favorite), Key 2, Key 3, Key 4,		
Physical Controls:	Key 5 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
WALL MOUNT			
VESA Compatible:	100 x 100 mm		

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.