

Key Features

- 165Hz refresh rate for smooth gameplay
- 1ms (MPRT) response time for precision
- FreeSync Premium prevents screen tearing
- Full HD resolution for high detail
- 1500R curved screen for immersion



Product **Description**

The ViewSonic VX2418C features a crisp Full HD display paired with a hyper-responsive 165Hz refresh rate for smooth gaming. The 1500R screen curvature provides a truly immersive viewing experience that lets you enjoy big, bold and stunning panoramic views. The 165Hz refresh rate loads more frames for sleek gameplay with less lag. A 1ms response time ensures your reactions are as fast as the game, helping you to claim more victories. FreeSync Premium virtually eliminates screen tearing and stuttering for the smoothest gaming experience possible.

DISPLAY		VIDEO INPUT	
Display Size (in.):	24	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)
Viewable Area (in.):	23.6	ERGONOMICS	
Panel Type:	VA Technology	Tilt (Forward/Back):	-5° / 20°
Resolution:	1920 x 1080	WEIGHT (IMPERIAL)	
Resolution Type:	FHD (Full HD)	Net (lbs):	6.8
Static Contrast Ratio:	3,000:1 (typ)	Net Without Stand (lbs):	5.7
Dynamic Contrast Ratio:	80M:1	Gross (lbs):	9.7
Light Source:	LED	WEIGHT (METRIC)	
Brightness:	250 cd/m² (typ)	Net (kg):	3.1
Colors:	16.7M	Net Without Stand (kg):	2.6
Color Space Support:	8 bit (6 bit + FRC)	Gross (kg):	4.4
Aspect Ratio:	16:9	DIMENSIONS (IMPERIAL) (V	WXHXD)
Response Time (MPRT):	1ms	Packaging (in.):	23.8 x 15.8 x 5.4
Viewing Angles:	178º horizontal, 178º vertical	Physical (in.):	21.3 x 16.3 x 8.2
Backlight Life (Hours):	30000 Hrs (Min)	Physical Without Stand (in.):	21.3 x 12.7 x 2.9
Curvature:	1500R	DIMENSIONS (METRIC) (WX	(HXD)
Refresh Rate (Hz):	165	Packaging (mm):	605 x 402 x 136
Variable Refresh Rate Technology:	FreeSync Premium	Physical (mm):	540 x 413 x 209
Blue Light Filter:	Yes	Physical Without Stand (mm):	540 x 322 x 74
Flicker-Free:	Yes	GENERAL	
Color Gamut:	NTSC: 72% size (Typ) sRGB: 102% size (Typ)	Regulations:	cTUVus, FCC-B, ICES003, CEC, CE CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA,
Pixel Size:	0.272 mm (H) x 0.272 mm (V)		BSMI
Surface Treatment: COMPATIBILITY	Anti-Glare, Hard Coating (3H)	PACKAGE CONTENTS:	VX2418C x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.2 Male-Male) x1, AC/DC Adapter x1,
	1920x1080		Quick Start Guide x1
PC Resolution (max):		Recycle/Disposal:	Please dispose of in accordance wit local, state or federal laws.
Mac® Resolution (max): PC Operating System:	1920x1080 Windows 10/11 certified; macOS tested	Warranty:	*Warranty offered may differ from market to market
Mac® Resolution (min):	1920x1080		
	102001000		
3.5mm Audio Out:	1		
HDMI 1.4:	2		
DisplayPort:	1		
Power in:	DC Socket (Center Positive)		
AUDIO	De socket (center rositive)		
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	15W		
Eco Mode (optimized):	19W		
Consumption (typical):	23W		
Consumption (max):	25W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	External Power Adaptor		
ADDITIONAL HARDWARE	External Fower Adaptor		
Kensington Lock Slot:	1		
CONTROLS			
Physical Controls:	U, R, D, L, EN (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual		
OBEDATING CONDITIONS	Image Adjust, Setup Menu		
	22°E to 104°E (0°C to 40°C)		
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing): WALL MOUNT	20% to 90%	_	
VESA Compatible:	100 x 100 mm		
INPUT SIGNAL Frequency Horizontal:	30 ~ 160KHz		
Frequency Vertical:	48 ~ 165Hz		