## Key **Features**

- 1500R curved screen for a perfect balance of immersion and comfort
- 144Hz refresh rate ensures clarify in motion
- 1ms (MPRT) response time ensures smooth images
- AMD FreeSync™ Premium prevents screen tearing
- QHD 1440p resolution for clear detail



## Product **Description**

With an ultimate immersive curved screen and 144Hz refresh rate, the ViewSonic VX2768-2KPC-MHD provides a stunning viewing experience. The monitor has been designed with a 1500R curved and borderless panel for an immersive experience. A high 144Hz refresh rate delivers clarity in motion while AMD FreeSync™ Premium, virtually eliminates screen tearing and stuttering for a fluid gaming experience. With 1ms MPRT response time, the monitor delivers smooth images without ghosting. The VX2768-2KPC-MHD is also equipped with ViewSonic's exclusive ViewMode™ presets, which offer user-customized game modes, including FPS, RTS and MOBA game settings. In addition, a DisplayPort and two HDMI inputs offer flexible connectivity for gameplay.

DISPLAY	-	INPUT SIGNAL	
Display Size (in.):	27	Frequency Horizontal:	30 ~ 255KHz
Viewable Area (in.):	27	Frequency Vertical:	48 ~ 144Hz
Panel Type:	VA Technology	VIDEO INPUT	
Resolution:	2560 x 1440	Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.2)
Resolution Type:	QHD (Quad HD)	ERGONOMICS	
Static Contrast Ratio:	3,000:1 (typ)	Tilt (Forward/Back):	-3° / 21°
Dynamic Contrast Ratio:	80M:1	WEIGHT (IMPERIAL)	
Light Source:	LED	Net (lbs):	11
Brightness:	250 cd/m² (typ)	Net Without Stand (lbs):	9.6
Colors:	16.7M	Gross (lbs):	14.9
Color Space Support:	8 bit (6 bit + FRC)	WEIGHT (METRIC)	
Aspect Ratio:	16:9	Net (kg):	5
Response Time (MPRT):	1ms	Net Without Stand (kg):	4.4
Viewing Angles:	178° horizontal, 178° vertical	Gross (kg):	6.8
Backlight Life (Hours):	30000 Hrs (Min)	DIMENSIONS (IMPERIAL) (W	
Curvature:	1500R	Packaging (in.):	26.8 x 18.4 x 6.5
Refresh Rate (Hz):	144	Physical (in.):	24 x 17.8 x 8.6
Adaptive Sync:	FreeSync	Physical (iii.):	24 x 14.5 x 3.1
Blue Light Filter:	Yes	DIMENSIONS (METRIC) (WX	
Flicker-Free:	Yes	Packaging (mm):	680 x 467 x 166
		Physical (mm):	610 x 452 x 219
Color Gamut:	NTSC: 85% size (Typ) sRGB: 120% size (Typ)	Physical (IIIII).  Physical Without Stand (mm):	610 x 367 x 78
Pixel Size:	0.233 mm (H) x 0.233 mm (V)	, , ,	610 X 367 X 78
Surface Treatment:	Anti-Glare, Hard Coating (3H)	GENERAL	aTIIVua ECC B ICESONA CEC TII
COMPATIBILITY		Regulations:	cTUVus, FCC-B, ICES003, CEC, TU S-Mark, MX-CoC, Mexico Energy
PC Resolution (max):	2560×1440		VX2768-2KPC-MHD x1, 3-pin Plug
Mac® Resolution (max):	2560x1440	PACKAGE CONTENTS:	(IEC C13 / CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, Quick Start Guide x1
PC Operating System:	Windows 7/8/8.1/10/11 certified; macOS tested 2560x1440	Recycle/Disposal:	Please dispose of in accordance wit local, state or federal laws.
Mac® Resolution (min):  CONNECTOR	2500X1440	Warranty:	*Warranty offered may differ from
3.5mm Audio Out:	1	·	market to market
		Country Of Origin:	40
HDMI 2.0:	2		
DisplayPort:	1		
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO			
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	30W		
Eco Mode (optimized):	36W		
Consumption (typical):	42W		
Consumption (max):	55W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
CONTROLS			
Physical Controls:	Joystick key: Up, Right, Down, Left, Center; Key 1 (favorite); Key 2 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Temperature: Humidity (non-condensing):	32°F to 104°F (0°C to 40°C) 20% to 90%		
Humidity (non-condensing):	20% to 90%		
Humidity (non-condensing):	, , ,		