




Key **Features**


All-in-One Solution | ViewBoard Interactive Flat Panel | Faster WiFi |

Fixed Wall Mount

Product **Description**

Ideal for education environments, this all-in-one ViewBoard Bundle includes a 75” ViewBoard IFP7550 4K interactive flat panel, a LB-WIFI-001 wireless AC adapter, and a WMK-047-2 wall mount.





1. Menu Controls
2. USB 2.0 Type A x2
3. USB 3.0 Type A
4. HDMI Out
5. USB 2.0 Type A
6. HDMI 1.4 In x2
7. USB 3.0 Type B
8. HDMI 2.0 In
9. Display Port In
10. PC Video/Audio In
11. USB 3.0 Type B
12. USB 3.0 Type A
13. Composite In
14. USB 2.0 Type A
15. SPDIF
16. Internal Speakers
17. VESA® Compatible Wall Mount 400 x 800 mm
18. RS232
19. LAN
20. Power Switch
21. AC In
22. Audio Out

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Display Size (in.):	75
Viewable Area (in.):	75
Light Source:	LED
Resolution:	3840 x 2160
Refresh Rate (Hz):	60
Aspect Ratio:	16:9
Static Contrast Ratio:	1,200:1
Dynamic Contrast Ratio:	5,000:1
Backlight Life (Hours):	50,000
Brightness:	350 cd/m2
Response Time (Typical GTG):	8ms
Viewing Angles:	178º horizontal, 178º vertical
Panel Surface:	9H
Operation Rating:	16/7

Networking:

Ethernet LAN:	10/100/1000 Mbps

Embedded Player:

OS:	ViewBoard OS (embedded Android 8)
GPU:	ARM Mali450 MP4
CPU:	ARM Quad Core A73 + A53
CPU Processor Speed:	A73: 1.1GHz, A53: 1.5GHz
Memory:	2GB
Storage:	16GB
Built-in Software:	myViewBoard, Chromium browser, Zoom, ViewBoard Cast

Audio:

Internal Speakers:	10W (x2)
Subwoofer:	15W (x1)

Connector:

HDMI 2.0 In(3), HDMI Out(1), VGA(1), DisplayPort(1), Composite RCA(1), 3.5mm Audio In(1), 3.5mm Audio Out(1), SPDIF Audio Out(1), USB 3.0(4), USB 2.0(3), Slot-in PC Slot(1), USB B Touch Port(2), RS232(1), Ethernet LAN (RJ45)(1), WIFI Module Slot(1)

Power:

Voltage:	100-240 VAC
Consumption (max):	350W
Consumption (typical):	138W
Stand-by:	<0.5W

Controls:

On Screen Display:	Input, Volume, Backlight, Audio, Screen, Display, Adjust
Remote Control:	Volume, Channel, Source, Mute, Back, Input, Menu

Operating Conditions:

Temperature:	32-104º F (0 - 40º C)
Humidity (non-condensing):	10-90%

Touch:

Touch Technology:	Infrared
Touch Points:	20-Point Touch
Tip Detection:	Dual tips, 3mm and 8mm

Weight (imperial):

Net (lbs):	143.1
Gross (lbs):	183.1

Weight (metric):

Net (kg):	64.9
Gross (kg):	83.1

Dimensions (imperial) (WxHxD):

Packaging (in.):	75.3 x 48.2 x 13.6
Physical (in.):	69.4 x 41.0 x 5.7

Dimensions (metric) (WxHxD):

Packaging (mm):	1919.0 x 1225.0 x 345.0
Physical (mm):	1763.0 x 1042.0 x 145.0

Mount:

VESA Compatible:	800 x 400 mm

General:

Warranty: 3-year limited warranty on parts, labor and backlight, onsite warranty

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

PACKAGE CONTENTS: IFP7550 Display, LB-WIFI-001, WMK-047-2, stylus pen x 2, power cable, remote control with batteries, ViewSonic Wizard CD (User Guide), Quick Start Guide, USB cable, camera bracket, HDMI cable, power cords

Regulations: cTUVus, FCC, ENERGY STAR 7.0, Mexico Energy, CE, CB, RoHS, ErP, WEEE

UPC: 766907002560

Accessories:

Intel Unite, LB-PEN-002, NMP660, PD-IFP-001, PD-IFP-002, PD-IFP-003, PD-IFP-004, SW-071, SW-072, SW-072-2, SW-073, SW-073-2, SW-074, SW-074-2, SW-075, SW-075-2, SW-101, SW-UP-117, VB-BLF-001, VB-BLM-001, VB-BLM-002, VB-BLM-003, VB-BLM-004, VB-CAM-001, VB-CAM-001-S, VB-EBM-001, VB-EBS-001, VB-EBT-001, VB-PEN-002, VB-STND-001, VB-STND-002, VB-STND-003, VB-STND-004, VB-STND-005, VB-VIS-001, VB-WKB-001, VBD100, VBH100, VBS100, VPC15-WP-4, VPC15-WP-6, VPC16-WP-4, VPC17-WP-6

Copyright © ViewSonic Corporation 2000-2021. All rights reserved. (08/25/2021 02:08 AM PST)