
Key **Features**

Everything within Reach | Enhanced Touchscreen Performance | myViewBoard™ Annotation Software | ViewBoard Cast Content Sharing Software | Enhanced Viewing Comfort



Product **Description**

Featuring 4K Ultra HD resolution and an advanced, next-generation touchscreen, the ViewSonic® ViewBoard® IFP8650 delivers incredible collaborative capabilities for 21st century boardrooms and classrooms. With integrated myViewBoard* annotation software and ViewBoard Cast streaming software, content creation and sharing has never been easier. What's more, this ENERGY STAR certified display delivers optional slot-in PC capability for more computing-intensive interactive applications. A VESA-compatible design allows for installation on a wall mount, or on an optional trolley cart for more flexible installation in classrooms and meeting rooms.



- 6. USB B Touch Port x2 7. HDMI 2.0 in 8. VGA 9. Audio In 10. SPDIF 11. RS232 1. Menu Controls 2. USB 2.0, USB 3.0 x2 3. VESA* Compatible Wall Mount 800 x 600 mm 4. HDMI Out 5. USB 3.0 x 3
- 03 0



RESOLUTION

20-Point TOUCH INTERACTIVE

all: 888.881.8781 **Contact Sales** — email: salesinfo@viewsonic.com visit: viewsonic.com

Display:

Display Type: LCD
Display Size (in.): 86
Viewable Area (in.): 85.6
Light Source: LED
Resolution: 3840 x 2160

Refresh Rate (Hz): 60
Aspect Ratio: 16:9
Static Contrast Ratio: 1,200:1
Dynamic Contrast Ratio: 5,000:1
Backlight Life (Hours): 50,000
Brightness: 350 cd/m2

Response Time (Typical GTG): 8ms

Viewing Angles: 178° horizontal, 178° vertical

Panel Surface: 9H Operation Rating: 16/7

Networking:

Ethernet LAN: 10/100/1000 Mbps

Embedded Player:

OS: ViewBoard OS (embedded Android 8)

CPU: ARM Quad Core A73 + A53
CPU Processor Speed: A73: 1.1GHz, A53: 1.5GHz

Memory: 3GB Storage: 32GB

Audio:

 Internal Speakers:
 10W (x2)

 Subwoofer:
 15W (x1)

Connector:

HDMI 2.0 In(3), VGA(1), 3.5mm Audio In(1), 3.5mm Audio Out(1), SPDIF Audio Out(1), USB 3.0(4), USB 2.0(3), Slot-in PC Slot(1), USB B Touch Port(2), RS232(1), Ethernet LAN (RJ45)(1), WIFI Module Slot(1)

Power:

Voltage: 100-240 VAC
Consumption (max): 350W
Consumption (typical): 155W

Operating Conditions:

Temperature: 32-104° F (0 - 40° C)

Humidity (non-condensing): 10-90%

Touch:

Touch Technology: Infrared
Touch Points: 20-Point Touch

Tip Detection: Dual tips, 3mm and 8mm

Weight (imperial):

Net (lbs): 153.7 Gross (lbs): 202.8 Weight (metric):

 Net (kg):
 69.7

 Gross (kg):
 92.0

Dimensions (imperial) (WxHxD):

Packaging (in.): 83.6 x 53.0 x 11.0 Physical (in.): 77.1 x 45.7 x 3.5

Dimensions (metric) (WxHxD):

Packaging (mm): 2123.0 x 1345.0 x 280.0 Physical (mm): 1958.0 x 1160.0 x 90.0

Mount:

VESA Compatible: 800 x 600 mm

General:

Warranty: 3-year limited warranty on parts, labor and backlight, onsite warranty

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

PACKAGE CONTENTS: IFP8650 display, stylus pen x 2, power cable, HDMI cable, USB cable, remote control with batteries, Camera plate, M8 screw x 8, Quick Start Guide

Regulations: cTUVus, FCC, ENERGY STAR, Mexico Energy, CE, CB, RoHS, ErP, WEEE

UPC: 766907002485

Accessories:

LB-WIFI-001, NMP660, PD-IFP-001, PD-IFP-002, PD-IFP-003, PD-IFP-004, SW-071, SW-072, SW-073, SW-074, SW-075, SW-101, VB-CAM-001, VB-STND-001, VB-STND-002, VB-STND-003, VB-STND-004, VB-VIS-001, VB-WKB-001, VPC15-WP-4, VPC15-WP-6, VPC16-WP-4, VPC17-WP-6, VPC25-W33-P1, VPC25-W53-P2, VPC27-W55-P2, WMK-047-2