


ZU820T Ultra bright professional laser projector



- 8800 lumen DuraCore laser projector Ultra bright for immersive installations
- Full motorized lens shift Ideal for a simple set-up
- Large zoom range Motorized zoom expands placement opportunities
- Long life Delivers 30,000 hours of virtually maintenance-free operation



At 8800 lumens with 4K and HDR compatibility, the ZU820T features a dust-resistant IP5X certified optical engine for 24/7 operation capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include motorized zoom and focus, full motorized lens shift and built-in dual 10W speakers.

High brightness, color precision and quiet operation, alongside a 1.6x zoom make this projector the ideal solution for a variety of end-user scenarios and professional environments, such as simulation, edge-blending and projection mapping, and immersive installations.

Specifications

)55387666245 Colour Black
JPC: 796435 44 601 7, EAN: 50	1000240, 0010ul. Diack
Display/image	
Display technology	DLP
Resolution	WUXGA (1920x1200)
Brightness	8,800 lumens
ANSI brightness	7,400
Contrast ratio	3,000,000:1
Contrast ratio - full on/off	1,100:1
lative aspect ratio	16:10
spect ratio - compatible	4:3,16:9,16:10
Leystone correction -	30°
orizontal	
Ceystone correction - vertical	30°
Jniformity	95%
creen size	50" ~ 300" diagonal
amp info	
ight source type	DuraCore Laser
ASER life	30,000 hours
ptical	
hrow ratio	1.25:1 ~ 2:1
Projection distance	31.5" - 846.46"
coom	1.6
oom type	Motorised
ocal length (mm)	18.72~29.59
ens shift	Vertical: +/-55%, Horizontal: +/-25%
ens shift	Yes - {{downloads_link}}
connectivity	100 - HorowingageTink}
Connections	Inputs 1 x HDBaseT, 1 x HDMI 2.0, 1 x HDMI 1.4a 3D
	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm
	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A,
	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm
•	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A,
onnections	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232
onnections AN - wireless networking	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x
onnections AN - wireless networking ieneral	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No
AN - wireless networking ieneral oise level (typical)	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB
onnections AN - wireless networking ieneral oise level (typical) oise level (max)	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB
connections AN - wireless networking General Ioise level (typical) Ioise level (max) D	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D
AN - wireless networking An - wireless networking D -	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock
onnections AN - wireless networking ieneral oise level (typical) oise level (max) D ecurity	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese,
AN - wireless networking An - wireless networking Aeneral loise level (typical) loise level (max) D ecurity ISD / display languages	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)
AN - wireless networking ieneral oise level (typical) oise level (max) D ecurity SD / display languages 4/7 operation	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes
AN - wireless networking AN - wireless networking Aeneral loise level (typical) loise level (max) D security JSD / display languages 4/7 operation 60° operation	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes
AN - wireless networking ieneral loise level (typical) loise level (max) D ecurity ISD / display languages 4/7 operation 60° operation lemote control	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes Backlit ProAV remote
AN - wireless networking eneral oise level (typical) oise level (max) D ecurity SD / display languages 4/7 operation 50° operation emote control peaker count	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2
AN - wireless networking ieneral loise level (typical) loise level (max) D ecurity ISD / display languages 4/7 operation 60° operation temote control peaker count /atts per speaker	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes Backlit ProAV remote
AN - wireless networking eneral oise level (typical) oise level (max) D ecurity SD / display languages 4/7 operation 60° operation emote control peaker count /atts per speaker letworking	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 10W
AN - wireless networking eneral oise level (typical) oise level (max) D ecurity SD / display languages 4/7 operation 60° operation emote control peaker count /atts per speaker etworking AN - wireless networking	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 10W
AN - wireless networking eneral oise level (typical) oise level (max) o ecurity SD / display languages 1/7 operation 50° operation emote control oeaker count fatts per speaker etworking AN - wireless networking	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 10W
AN - wireless networking eneral oise level (typical) oise level (max) o ecurity SD / display languages 4/7 operation 50° operation emote control peaker count fatts per speaker etworking AN - wireless networking AN	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes Backlit ProAV remote 2 10W No Yes
AN - wireless networking ieneral oise level (typical) oise level (max) D ecurity SD / display languages 4/7 operation 60° operation emote control peaker count /atts per speaker etworking AN - wireless networking AN ower ower ower supply	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes Backlit ProAV remote 2 10W No Yes AC 90 – 264V 50/60 Hz with PFC input
AN - wireless networking ieneral loise level (typical) loise level (max) D ecurity VSD / display languages 4/7 operation 60° operation lemote control peaker count /atts per speaker letworking AN - wireless networking AN Power ower supply	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes Backlit ProAV remote 2 10W No Yes
AN - wireless networking eneral loise level (typical) loise level (max) D ecurity ISD / display languages 4/7 operation 60° operation temote control peaker count /atts per speaker letworking AN - wireless networking AN 'ower ower supply ower consumption (standby)	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes Backlit ProAV remote 2 10W No Yes AC 90 – 264V 50/60 Hz with PFC input
AN - wireless networking ieneral ioise level (typical) ioise level (max) D ecurity ISD / display languages 4/7 operation 60° operation temote control peaker count /atts per speaker letworking AN - wireless networking AN - ower supply ower consumption (standby) ower consumption (min)	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 10W No Yes AC 90 – 264V 50/60 Hz with PFC input 0.5W
AN - wireless networking ieneral oise level (typical) oise level (max) D ecurity SD / display languages 4/7 operation 60° operation emote control peaker count /atts per speaker letworking AN - wireless networking AN - ower ower supply ower consumption (standby) ower consumption (max)	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 10W No Yes AC 90 – 264V 50/60 Hz with PFC input 0.5W 260W
AN - wireless networking eneral oise level (typical) oise level (max) D ecurity SD / display languages 4/7 operation 50° operation emote control peaker count /atts per speaker letworking AN - wireless networking AN - wireless networking	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Backlit ProAV remote 2 10W No Yes AC 90 – 264V 50/60 Hz with PFC input 0.5W 260W
AN - wireless networking An - wireless networking General loise level (typical) loise level (max) D security SSD / display languages 4/7 operation	support, 1 x VGA, 1 x 3D sync, 1 x Audio 3.5mm Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A, 1 x Audio 3.5mm Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x RS232 No 34dB 36dB Full 3D Security bar, Kensington Lock 10 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes Yes Backlit ProAV remote 2 10W No Yes AC 90 – 264V 50/60 Hz with PFC input 0.5W 260W 520W







Copyright © 2023 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas InstrumentsTM. All other trademarks are the property of their respective owners. All specifications subject to change at any time. 10032023050654