

Deliver perfect presentations with this meeting room solution offering excellent brightness, stream and share features and HDBaseT technology.

With WXGA resolution and an outstanding brightness level of 5,500 lumens, bring sharp images and bright colours to any meeting room with the EB-2165W. Designed to provide a scalable image up to a massive 300 inches, it offers a wide range of connectivity options including HDBaseT, Screen Mirroring and Wireless LAN connectivity, and Gesture Presenter for intuitive control.

Up to 300-inch display and outstanding quality

WXGA resolution combined with Epson's 3LCD technology ensures high-quality content has more vivid colours and brighter images. HDMI connectivity guarantees sharper and clearer content, even at the maximum image size of 300 inches.

HDBaseT Connectivity

The EB-2165W offers a wide range of connectivity options, including HDBaseT, Screen Mirroring, two HDMI inputs, and Wireless LAN connectivity for PCs and mobile devices. HDBaseT provides Full HD video, audio and Ethernet connectivity via one cable to enable control from 100 metres away.

Home screen

The home screen offers quick and easy access to a variety of useful functions, such as connection sources. Wireless connections can also be made easily using the information on screen.

Gesture Presenter

Change slides by simply moving your hand, making even smarter presentations a reality by liberating the user from their remote control or mouse.

Auto Power On

The projector will start-up automatically upon connecting an HDMI, VGA, or USB cable to the connected device, meaning you no longer have to use the power button on the remote control.

KEY FEATURES

- Up to 300-inch display and great quality
- WXGA resolution with Epson's 3LCD technology
- Project bold images even in bright rooms
 - Outstanding 5,500-lumen brightness
- Extensive connectivity options HDBaseT, Screen Mirroring and Wireless LAN, as well as dual HDMI
- Flexible interaction Split screen and Multi-PC Projection
- Gesture Presenter Intuitively use gestures to control presentations





PRODUCT SPECIFICATIONS

TECHNOLOGY		
Projection System	3LCD Technology, RGB liquid crystal shutter	
LCD Panel	0.76 inch with D8	
IMAGE		
Color Light Output	5,500 Lumen- 3,800 Lumen (economy) In accordance with ISO 21118:2013	
White Light Output	5,500 Lumen - 3,800 Lumen (economy) In accordance with ISO 21118:2013	
Resolution	WXGA, 1280 x 800, 16:10	
Aspect Ratio	16:10	
Contrast Ratio	15,000 : 1	
Light source	Lamp	
Lamp	300 W, 5,000 h durability, 10,000 h durability (economy mode)	
Keystone Correction	Auto vertical: \pm 30 °, Auto horizontal \pm 20 °	
Colour Video Processing	10 Bits	
2D Vertical Refresh Rate	100 Hz - 120 Hz	
Colour Reproduction	Upto 1.07 billion colours	
ODTICAL		
OPTICAL Throw Ratio	1.38 - 2.28:1	
Zoom		
Lens	Manual, Factor: 1 - 1.6 Optical	
	•	
Screen Size	30 inches - 300 inches	
Projection Distance Wide	0.9 m (30 inch screen	
Projection Distance Tele	9 m (300 inch screen	
Projection Lens F Number	1.51 - 1.99	
Projection Lens Focal Length		
Projection Lens Focus	Manual	
Offset	10:1	
CONNECTIVITY		
USB Display Function	3 in 1: Image / Mouse / Sound	
Interfaces	USB 2.0 Type A, USB 2.0 Type B, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), VGA	
	in (2x), VGA out, HDMI in (2x), Composite in, RGB in (2x), RGB out, HDBaseT, MHL, Stereo	
	mini jack audio out, Stereo mini jack audio in (2x), Miracast, Wireless LAN b/g/n (2.4GHz),	
	Wireless LAN IEEE 802.11a/b/g/n/ac	
Epson iProjection App	Ad-Hoc / Infrastructure	
ADVANCED FEATURES		
Security	Kensington lock, Security bar, Control panel lock, Password lock, Padlock, Wireless LAN unit	
coounty	lock, Wireless LAN security, Password protection	
2D Colour Modes	Dynamic, Cinema, Presentation, sRGB, Blackboard, DICOM SIM	
Other features	AV Mute Slide, Auto Power On, Automatic input selection, Automatic keystone correction,	
Other features	Built-in speaker, CEC compatible, Direct Power on/off, Document Camera Compatible, Fit to	
	Screen, Freeze image, Gesture Presenter, Home Screen, JPEG Viewer, Long lamp life, MHL	
	audio/video interface, Network administration, OSD copy function, PC Free, Projection App for	
	Chromebook, Quick Corner, Screen Mirroring, Slide show, Split-Screen-Function, Wireless	
Video Color Modes	LAN capable, iProjection App	
	Blackboard, Dynamic, Photo, Presentation, sRGB, DICOM SIM	
Projector control	via: AMX, Crestron, Control4	

EB-2165W

WHAT'S IN THE BOX

- Computer cable
- Power cable
- Remote control incl. batteries
- Software (CD)
- Wireless LAN unit
- User Manual (CD-ROM)
- Main unit





PRODUCT SPECIFICATIONS

GENERAL		W	
Power consumption	425 Watt, 323 Watt (economy), 0.5 Watt (standby)		
Supply Voltage	AC 220 V - 240 V, 50 Hz - 60 Hz		
Product dimensions	377 x 291 x 110 mm (Width x Depth x Height)	• (
Product weight	roduct weight 4.6 kg		
Noise Level	Normal: 39 dB (A) - Economy: 29 dB (A)		
Supported Temperature	nperature Operation 5° C - 40° C, Storage -10° C - 60° C		
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%	• 5	
	If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could break and cause the projector to drop from the ceiling.	● \ ● (● N	
	If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance.		
Included Software	EasyMP Monitor, iProjection		
Options	HDBaseT Transmitter, Soft carry case		
Loudspeaker	16 Watt		
Room Type / Application	Boardroom, Large Meeting Room / Auditorium		
Positioning	Ceiling Mounted, Desktop		
Colour	White		
OTHER			
Warranty	60 months Carry in or 8,000 h, Lamp: 60 months or 1,000 h		
	Optional warranty extension available		

EB-2165W

WHAT'S IN THE BOX

- Computer cable
- Power cable
- Remote control incl. batteries
- Software (CD)
- Wireless LAN unit
- User Manual (CD-ROM)
- Main unit



OPTIONAL ACCESSORIES

- Air Filter ELPAF41
 V13H134A41
- Wireless LAN Adapter ELPAP10 V12H731P01
- Soft Carry Case ELPKS68 V12H001K68
- Ceiling Mount (White) ELPMB23 V12H003B23
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14
- HDBaseT Transmitter ELPHD01 V12H547040
- ELPLP95
- V13H010L95
- Control and Connection Box ELPCB02 V12H614040

LOGISTICS INFORMATION

SKU	V11H817040 V11H817041
EAN code	8715946628523
Country of Origin	China
Layer	4 Units

EB-2165W



