# **EB-2247U**

#### **DATASHEET / BROCHURE**

















Deliver perfect Full HD presentations with this display solution, offering a brightness of 4,200 lumens with wireless and screen mirroring connectivity.

Offers an outstanding brightness 4,200 lumens and Full HD resolution with the EB-2247U, designed to display a scalable image size of up to 300 inches, and offers connectivity options such as dual HDMI and wireless LAN connectivity as standard.

## Outstanding quality display of up to 300 inches

Full HD resolution combined with Epson's 3LCD technology ensures high-quality content has more vivid colours and brighter images. HDMI connectivity guarantees sharper and clearer presentations delivered on a scalable image size of up to 300 inches.

# Simple set-up and multiple connectivity

The EB-2247U offers a wide range of connectivity options, including screen mirroring, wireless LAN and two HDMI inputs. Set-up is easy too, thanks to features including auto-power-on, focus help, keystone correction and screen fit - delivering presentations quickly and efficiently. Compatible with iProjection software for easy connectivity with mobile devices.

# Home screen

The home screen offers quick and easy access to a variety of useful functions, such as choosing connection sources. Wireless connections can also be made easily using the information on screen.

#### Value-added flexibility

The Multi-PC projection software bundled with the EB-2247U makes it possible to connect up to 50 computers and partition the screen for split-screen projection capability - offering far better cost-effectiveness and flexibility than a flat-panel display.

## **KEY FEATURES**

Up to 300-inch display and great quality

Full HD resolution with Epson's 3LCD technology

- Be professional 4,200-lumen brightness
- Extensive connectivity options
   Including wireless LAN, screen mirroring, as well as dual HDMI
- Flexible interaction

  Split screen and multi-PC projection
- Long lamp life
  Up to 12,000 hours in eco mode





#### PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology, RGB liquid crystal shutter

LCD Panel 0.67 inch with D10

IMAGE

Color Light Output 4,200 Lumen- 2,410 Lumen (economy) In accordance with ISO 21118:2013
White Light Output 4,200 Lumen - 2,410 Lumen (economy) In accordance with ISO 21118:2013

Resolution WUXGA, 1920 x 1200, 16:10

High Definition Full HD
Aspect Ratio 16:10
Contrast Ratio 15,000 : 1
Light source Lamp

Lamp 230 W, 5,500 h durability, 12,000 h durability (economy mode)

Keystone Correction Auto vertical: ± 30 °, Auto horizontal ± 30 °

Colour Video Processing 10 Bits
2D Vertical Refresh Rate 200 Hz - 240 Hz
Colour Reproduction Upto 1.07 billion colours

OPTICAL

Throw Ratio 1.39 - 2.23:1
Zoom Manual, Factor: 1 - 1.6

Lens Optical

Screen Size 30 inches - 300 inches Projection Distance Wide 1.5 m ( 45 inch screen Projection Distance Tele 8.9 m ( 260 inch screen

 Projection Lens F Number
 1.5 - 2

 Projection Lens Focal Length
 23 mm - 38.4 mm

 Projection Lens Focus
 Manual

 Offset
 27 : 1

CONNECTIVITY

USB Display Function 3 in 1: Image / Mouse / Sound

Interfaces USB 2.0 Type A, USB 2.0 Type B, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T),

Gigabit ethernet interface, VGA in (2x), VGA out, HDMI in (2x), Composite in, RGB in (2x), RGB out, MHL, Stereo mini jack audio out, Stereo mini jack audio in (2x), Miracast, Wireless LAN

IEEE 802.11a/b/g/n/ac

Epson iProjection App Ad-Hoc / Infrastructure

ADVANCED FEATURES

Security Kensington lock, Security bar, Control panel lock, Password lock, Padlock, Wireless LAN unit

lock, Wireless LAN security, Password protection

2D Colour Modes Dynamic, Cinema, Presentation, sRGB, Blackboard

Other features AV Mute Slide, Auto Power On, Automatic input selection, Automatic keystone correction,

Built-in speaker, CEC compatible, Direct Power on/off, Document Camera Compatible, Freeze image, JPEG Viewer, Long lamp life, MHL audio/video interface, Network administration, OSD copy function, PC Free, Projection App for Chromebook, Quick Corner, Screen Mirroring, Slide

show, Split-Screen-Function, Wireless LAN capable, iProjection App

Video Color Modes Blackboard, Dynamic, Photo, Presentation, sRGB, DICOM SIM

Projector control via: AMX, Crestron, Control4

#### EB-2247U

#### WHAT'S IN THE BOX

- Computer cable
- Power cable
- Remote control incl. batteries
- Software (CD)
- User Manual (CD-ROM)
- Wireless LAN unit
- Warranty card
- Main unit





#### PRODUCT SPECIFICATIONS

**GENERAL** 

Power consumption 331 Watt, 227 Watt (economy), 2 Watt (standby)

Supply Voltage AC 220 V - 240 V, 50 Hz - 60 Hz

Product dimensions 309 x 282 x 90 mm (Width x Depth x Height)

Product weight 3.2 kg

Noise Level Normal: 37 dB (A) - Economy: 29 dB (A) Supported Temperature Operation  $5^{\circ}$  C -  $35^{\circ}$  C, Storage - $10^{\circ}$  C -  $60^{\circ}$  C Supported Humidity Operation 20% - 80%, Storage 10% - 90%

If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could

break and cause the projector to drop from the ceiling.

If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional

assistance.

Included Software EasyMP Monitor, iProjection

Options Soft carry case Loudspeaker 16 Watt

Room Type / Application Boardroom, Large Meeting Room / Auditorium

Positioning Ceiling Mounted, Desktop

Colour White

OTHER

Warranty 60 months Carry in, Lamp: 60 months or 1,000 h

Optional warranty extension available

#### EB-2247U

# WHAT'S IN THE BOX

- Computer cable
- Power cable
- Remote control incl. batteries
- Software (CD)
- User Manual (CD-ROM)
- Wireless LAN unit
- Warranty card
- Main unit



# **OPTIONAL ACCESSORIES**

EB-2247U

- V13H010L96
- Air Filter ELPAF32
- V13H134A32
- Soft Carry Case ELPKS70 V12H001K70
- Ceiling Mount (White) ELPMB23 V12H003B23
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14
- Active Speakers (2 x 15W) ELPSP02 V12H467040
- Air Filter ELPAF54 V13H134A54
- Safety Wire ELPWR01 V12H003W01

# **LOGISTICS INFORMATION**

SKU	V11H881040 V11H881041
EAN code	8715946642727
Country of Origin	Philippines
Layer	6 Units





