EB-800F



DATASHEET / BROCHURE





















The EB-800F is a bright and scalable ultra-short-throw display solution that brings Epson innovation to signage applications.

This laser display solution brings informative signage to life and produces scalable projections of up to 130 inches. It brings a fresh dimension to signage with borderless images and projection onto ultra-wide surfaces, including glass and curved walls. The EB-800F features Full HD 1080p image quality and delivers powerful and informative displays for retail, hospitality and visitor attractions.

Innovative and cost effective

Epson's advanced laser technology is robust and reliable, providing a fit-and-forget digital signage solution. It offers bright and vivid colours in a cost-effective solution that's capable of large display sizes.

Large and scalable images

The EB-800F enables scalable display sizes of up to 130 inches, in Full HD resolution with 5,000 lumen brightness and 3LCD technology for bright colours and high display quality even in bright spaces.

Versatile and easy to install

This sleek, stylish and bright display solution offers the flexibility to fulfil the most exacting brief, and the versatility to work in tight spaces. It can be mounted on the wall, ceiling, floor, or even hidden away to create added mystery. Its ultrashort-throw design enables projection of large images from a short distance. A black version is also available.

Flexible playback options

Content can be played directly from a USB stick, including: playlists, videos, and signage content using the built-in content playback feature and Epson Projector Content Manager software. Users can benefit from multi-projector and daisy-chain support for built-in edge blending, or illuminate an entire wall with one huge image. Also, the split screen feature allows users to connect multiple input sources to display different content sources simultaneously.

KEY FEATURES

- Ultra-short-throw signage projector Compact, unobtrusive design.
- Up to 130-inch display
 Full HD resolution, 5,000 lumen
 brightness and 3LCD technology
- Fit and forget reliability
 Low maintenance laser projector with a 5 year warranty
- Easy installation
 360 degree rotation with portrait projection support
- Flexible playback
 Play content directly from a USB stick





PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology
LCD Panel 0,62 inch with C2 Fine

IMAGE

Color Light Output 5.000 Lumen - 3.500 Lumen (economy)
White Light Output 5.000 Lumen - 3.500 Lumen (economy)
Resolution Full HD 1080p, 1920 x 1080, 16:9

Aspect Ratio 16:9

Contrast Ratio Over 2.500.000 : 1

Light source Lase

Laser Light source 20.000 hours Durability High, 30.000 hours Durability Eco

Keystone Correction Manual vertical: \pm 3 °, Manual horizontal \pm 3 °

Colour Video Processing 10 Bits
2D Vertical Refresh Rate 192 Hz - 240 Hz
Colour Reproduction Upto 1.07 billion colours

OPTICAL

Throw Ratio 0,27 - 0,37:1
Zoom Digital, Factor: 1 - 1,35

Lens Optical

Screen Size 65 inches - 130 inches
Projection Distance Wide 0,4 m (65 inch screen
Projection Distance Tele 0,8 m (130 inch screen

Projection Lens F Number 1,5
Projection Lens Focul Length 3,9 mm
Projection Lens Focus Manual
Offset 9:1

CONNECTIVITY

Interfaces USB 2.0 Type A (2x), USB 2.0 Type B, Powered USB, RS-232C, Ethernet interface (100 Base-

TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac (optional), VGA in (2x), VGA out, HDMI in (3x), HDMI out, Composite in, HDBaseT, Miracast (optional), Stereo mini jack audio out, Stereo

mini jack audio in (3x)
Ad-Hoc / Infrastructure

Epson iProjection App Ad-Hoc / Infrastructure

Network Protocol HTTPS, IPv6, SNMP, ESC/VP.net, PJLink

ADVANCED FEATURES

Security Kensington lock, Password lock, Padlock, Security cable hole, Password protection
Other features A/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, Cus

A/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, Customizable user logo, Daisy chain Multi-Projection, Digital zoom, Direct Power on/off, Document Camera Compatible, Driverless installation, Edge Blending, Email notification, Home Screen, Horizontal and vertical keystone correction, Image Shift, JPEG Viewer, Long light source life, Network administration, Network projection, OSD copy function, PC Free, Power on button, Quick Corner, Schedule Function, Split-Screen-Function, Ultra-wide display (16:6), Web

Control, Web Remote, iProjection App

Video Color Modes Blackboard, Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection

Projector control via: Crestron Integrated Partner, Crestron RoomView, Extron IP Link, Extron XTP, AMX Device

Discovery, Control4 Simple Device Discovery Protocol

EB-800F

WHAT'S IN THE BOX

- CD Manual
- Remote control incl. batteries
- Cable cover
- Power cable
- Warranty document
- Lens cap





PRODUCT SPECIFICATIONS

EB-800F

GENERAL

Power consumption 366 Watt, 262 Watt (economy), 0,5 Watt (standby)

Heat Dissipation 1.244 BTU/hour (max)
Supply Voltage AC 220 V - 240 V, 50 Hz - 60 Hz

Product dimensions 458 x 375 x 210 mm (Width x Depth x Height)

Product weight 9,4 kg

Noise Level Normal: 36 dB (A) - Economy: 27 dB (A)

Supported Temperature Storage -10 $^{\circ}$ C - 60 $^{\circ}$ C

Supported Humidity Operation 20% - 80%, Storage 10% - 90%

If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could

break and cause the projector to drop from the ceiling.

If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional

assistance.

Included Software Content DIY App, iProjection, Epson Projector Content Manager, Epson Projector

Management

Options Wireless LAN unit
Loudspeaker 8 Watt, Stereo: Stereo

Room Type / Application Signage / Retail, Visitor Attraction
Positioning Ceiling Mounted, Desktop, Wall Mounted

Colour White

TCO Certified For further information relating to TCO Certified please visit

https://tcocertified.com/files/certification/Information-document-for-end-users.pdf

OTHER

Warranty 60 months Carry in or 12.000 h



OPTIONAL ACCESSORIES

EB-800F

- Active Speakers (2 x 15W) ELPSP02 V12H467040
- Control and Connection Box ELPCB03 V12H927040
- HDBaseT Transmitter ELPHD01 V12H547040
- Dual Function Wireless Adapter (5Ghz Wireless & Miracast) -ELPAP11 V12H005A01
- Air Filter ELPAF56 L600/EB-14XX Series V13H134A56
- Wall Mount ELPMB62 EB-7xx / EB-8xx V12HA06A06

LOGISTICS INFORMATION

SKU	V11H923540
EAN code	8715946688992
Country of Origin	China





