

EB-G7000W

DATASHEET / BROCHURE



Easy to set-up and with low maintenance requirements, this 6,500-lumens WXGA installation projector boasts bright images and vivid colours.

Ideal for professional-looking presentations in a variety of large venues, the EB-G7000W creates images with rich, vivid colours thanks to Epson's 3LCD technology and equally high White and Colour Light Output. With flexible installation and low maintenance, this projector offers a fit-and-forget solution for scenarios in which only superior projections will do.

Superior image quality

Ensure superb quality and the best possible delivery of presentations with this powerful installation projector for large venues. Featuring Epson's own 3LCD technology and equally high White and Colour Light Output, WXGA resolution images are vivid and bright, even in daylight with its 6,500 lumens brightness.

Easy positioning

Thanks to a new range of motorised lenses, including optional ultra-short throw (UST) lens, and both vertical and horizontal lens shift, the projector benefits from true 360° installation flexibility allowing it to be placed almost anywhere.

Quick set-up

Get started quickly thanks to a lens memory function, which stores projector settings such as image position, focus and zoom, for prompt access when projecting images in different aspect ratios, or using different lenses. Split-screen allows dual feeds to be projected, while a portrait projection mode is possible without changing the lamp. For integration with a wide range of systems, inputs include HDMI, HDBaseT, DVI-D and component video.

KEY FEATURES

- **Superior picture quality**
3LCD technology; superior white balance; better colour matching
- **Expand installation possibilities**
Works with a wide range of optional lenses including ultra-short-throw
- **Flexible 360° installation**
True flexibility without distortion or loss of brightness
- **Lens memory function**
Stores projector settings such as image position, focus and zoom
- **Portrait projection mode**
Switch mode without having to change the lamp



EPSON®
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System	3LCD Technology
LCD Panel	0.76 inch with C2 Fine

IMAGE

Color Light Output	6,500 Lumen- 5,915 Lumen (economy) In accordance with IDMS15.4
White Light Output	6,500 Lumen - 5,915 Lumen (economy) In accordance with ISO 21118:2012
Portrait Colour Light Output	5,850 lm
Portrait White Light Output	5,850 lm
Resolution	WXGA, 1280 x 800, 16:10
Aspect Ratio	16:10
Contrast Ratio	50,000 : 1
Native Contrast	2,000 : 1
Lamp	400 W, 3,000 h durability, 4,000 h durability (economy mode)
Lamp (portrait mode)	400 Watt, 2,000 hours Durability
Keystone Correction	Manual vertical: $\pm 45^\circ$, Manual horizontal $\pm 30^\circ$
Colour Video Processing	10 Bits
Colour Reproduction	Upto 1.07 billion colours

OPTICAL

Throw Ratio	1.44 - 2.33:1
Zoom	Motorized, Factor: 1 - 1.6
Lens Shift	Motorized - Vertical $\pm 67\%$, horizontal $\pm 30\%$
Lens position memory	10 positions
Screen Size	50 inches - 300 inches
Projection Distance Wide	1.5 m - 9.4 m (50 inch screen
Projection Distance Tele	2.5 m - 15.1 m (50 inch screen
Projection Lens F Number	1.7 - 2.3
Projection Lens Focal Length	24 mm - 38.2 mm
Projection Lens Focus	Motorized

CONNECTIVITY

Interfaces	USB 2.0 Type A, USB 2.0 Type B (Service Only), RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11a/b/g/n (optional), VGA in, VGA out, DVI in, BNC in, HDBaseT, Stereo mini jack audio out, Stereo mini jack audio in (3x), HDMI (HDCP 2.2)
------------	---

ADVANCED FEATURES

Security	Kensington lock, Control panel lock, Password protection
Other features	4K enhancement, Built-in speaker, Document Camera Compatible, Lens position memory
Video Color Modes	Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection
Projector control	via: AMX, Crestron, Control4

GENERAL

Power consumption	515 Watt, 477 Watt (economy), 0.3 Watt (standby)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	525 x 472 x 189 mm (Width x Depth x Height)
Product weight	12.7 kg
Noise Level	Normal: 39 dB (A) - Economy: 31 dB (A)
Supported Temperature	Storage -10° C - 60° C
Supported Humidity	Operation 20% - 80%, Storage 10% - 90%
	If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could break and cause the projector to drop from the ceiling.
	If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional assistance.
Options	Document camera, Quick wireless USB key, Wireless LAN unit
Colour	White

OTHER

Warranty	36 months Carry in or 20,000 h, Lamp: 12 months or 1,000 h Optional warranty extension available
----------	---

EB-G7000W

WHAT'S IN THE BOX

- Cable cover
- Computer cable
- Lens cap
- Remote control incl. batteries
- User's Manual Set
- Power cable

OPTIONAL ACCESSORIES

EB-G7000W

- Air Filter - ELPAF30
V13H134A30
- ELPLP93
V13H010L93
- Wireless LAN Adapter - ELPAP10
V12H731P01
- HDBaseT Transmitter - ELPHD01
V12H547040
- 3D Polarizer - ELPPL01
V12H618A01
- Ceiling Mount (White) - ELPMB22
V12H003B22
- Ceiling Pipe (450mm) - ELPFP13
V12H003P13
- Ceiling Pipe (700mm) - ELPFP14
V12H003P14

OPTIONAL LENSES

- Lens - ELPLX01 - UST lens G7000 series & L1100,1200,1300,1400/5U
V12H004X01
- Lens - ELPLU04 - G7000 & L1000 Series ST off axis 2
V12H004U04
- Lens - ELPLW05 - G7000 & L1000 Series wide zoom 1
V12H004W05
- Lens - ELPLM08 - Mid throw 1 - G7000/L1000 series
V12H004M08
- Lens - ELPLL08 - Long throw - G7000/L1000 series
V12H004L08
- Lens - ELPLM10 - Mid throw 3 - G7000/L1000 series
V12H004M0A
- Lens - ELPLM11 - Mid throw 4 - G7000/L1000 series
V12H004M0B
- Lens - ELPLM15 - Mid Throw L1500/L1700 Series
V12H004M0F
- Lens - ELPLX01W - UST lens G7000 series & L1100,1200,1300,1400/5U
V12H004Y01
- Lens - ELPLU03S - L & G Series ST off axis 1
V12H004UA3

LOGISTICS INFORMATION

SKU	V11H752041 V11H752040
EAN code	8715946612195
Country of Origin	China
Layer	2 Units

Epson Middle East
P.O.Box 17383, Dubai
United Arab Emirates
Telephone: +9714 8818934

Hotline Telephone: +9714 8872172
Fax: +9714 8818945
E-mail: supportme@epson.co.uk
www.epson.ae

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

EPSON®