

DISCONTINUED

Pro G7500U WUXGA 3LCD Projector w/ 4K Enhancement & Standard Lens



Bright large-venue projector with 4K Enhancement, powered lenses and HDBaseT™.

The Pro G7500U large-venue projector delivers uncompromising image quality and native WUXGA performance with Epson® 4K Enhancement Technology[†]. Offering high Color Brightness*, Epson 3LCD projectors ensure vivid images. Ideal for events staging, auditoriums and sanctuaries, the versatile G7500U features 6500 lumens of color brightness and 6500 lumens of white brightness¹. Innovative 4K Enhancement Technology[†] ensures extraordinary image and video quality, while dynamic projection capabilities enable a range of applications. And, its outstanding integration features include diverse connectivity such as HDBaseT and nine optional powered lenses with lens shift and lens memory (Ships with Middle#1 Lens - V12H004M08).

High Color Brightness with Epson*

Brilliant image quality requires high color brightness. Epson 3LCD projectors have 100% Balanced Color Brightness and White Brightness*. Delivering 6500 lumens of color brightness¹ and 6500 lumens of white brightness¹, the PowerLite Pro G7500U uses 3LCD, 3-chip technology for brilliant images with true-to-life color.

Projection System: High-aperture Epson 3-chip 3LCD technology

Native Resolution: WUXGA (1920 x 1200) w/ 4K Enhancement Technology[†]

Color Brightness: 6500 lumens¹

White Brightness: 6500 lumens¹

Throw Distance Calculator

Model: V11H750020

Overview

Bright and Colorful

Features 6500 lumens of color brightness (color light output)¹ and 6500 lumens of white brightness (white light output)¹.

4K Enhancement Technology

Epson's 4K Enhancement Technology delivers astonishing picture quality — every subtle intricacy is captured.

HDBaseT

Combines HDMI, ethernet and RS-232 into one cable

Advanced Edge Blending

Get seamless panoramic, multi-screen edge blending on horizontal or vertical walls, with curved surface and corner wall support.

Optional Lenses

Interchangeable lens options with varying ranges for optimal placement and flexibility

Edge Blending

Use multiple projectors to overlap images, and there are no bright spots where the overlap occurs — providing dynamic, seamless projection.

- **High Color Brightness* and reliable performance** — 3LCD, 3-chip technology
- **One measurement of brightness is not enough** — look for both high color brightness and high white brightness.
The PowerLite Pro G7500U has:
Color Brightness: 6500 lumens¹
White Brightness: 6500 lumens¹
- **Exceptional Full HD widescreen display** — native WUXGA (1920 x 1200) with 4K Enhancement[†] for presentations, videos, digital signage and more
- **Innovative 4K Enhancement Technology[†]** — doubles the number of pixels from 2.3 million (WUXGA) to 4.6 million for extraordinary image and video quality
- **Nine optional interchangeable lenses** — with powered lens shift and lens memory, including an ultra short-throw lens for shallow spaces (standard lens included)
- **Versatile connectivity** — supports the full range of inputs, including HDBaseT, HDMI[™], DVI-D, VGA and 5-BNC, for easy integration with any system
- **Advanced collaboration features** — simultaneously project side-by-side from different sources with Split Screen²
- **Web-based remote management** — control and monitor projector status via a Web browser
- **Multi-PC Projection** — connect up to 50 Windows®, Mac®, iOS® or Android devices and display up to four screens simultaneously over the network (controlled via the Moderator³ function)
- **Dynamic projection capabilities** — advanced built-in Edge Blending, image warping and curved-surface correction technologies for a variety of applications
- **Epson Warranty** — Three-year limited warranty, Epson Road Service Program, Epson PrivateLine® dedicated toll-free support (U.S. and Canada only) and 90-day limited lamp warranty

Eco Features

- RoHS compliant
- Recyclable product⁴
- Epson America, Inc. is a SmartWay™ Transport Partner⁵

Better Products for a Better Future™

For more information on Epson's environmental programs, go to www.epson.com/environment

IMPORTANT SAFETY INFORMATION ABOUT USAGE ENVIRONMENTS FOR MOUNTED PROJECTORS ►

Specifications ►

Specifications Projector:

Projection System:

High-aperture Epson 3-chip, 3LCD technology

Projection Method:

Front / rear / ceiling mount

Driving Method:

Epson Poly-silicon TFT Active Matrix

Pixel Number:

2,304,000 dots (1920 x 1200) x 3

Color Brightness - Color Light Output:

6500 lumens¹

White Brightness - White Light Output:

6500 lumens¹

Aspect Ratio:

Supports 4:3, 16:9, 16:10

Resolution:

1920 x 1200 (WUXGA)

Resize:

640 x 480, 800 x 600, 1280 x 1024, 1400 x 1050

Lamp Type:

400 W UHE

Lamp Life:

- Normal mode: Up to 3000 hours²
- ECO mode: Up to 4000 hours²

Brightness Uniformity:

(typical) 90%

Pixel Arrangement:

Cross stripe

Throw Ratio Range:

(For Standard Lens) 1.44 – 2.32

Size - projected distance:

50" – 300"

Keystone Correction:

(For Standard Lens)

- Horizontal: ± 30 degrees
- Vertical: ± 45 degrees

Color Reproduction:

Up to 1 billion colors

Effective Scanning Frequency Range:

Pixel Clock, Horizontal, Vertical:Pixel Clock

- 13.5 MHz – 162 MHz (up to UXGA 60 Hz)

Horizontal

- 15 KHz – 92 KHz

Vertical

- 50 Hz – 85 Hz

General:

Temperature:

32° to 113° F (0° to 45° C)

Weight:

28.4 lb (with standard lens)

Security:

- Security cable hole
- Lens lock
- Kensington® lock provision,

Projection Lens:

Type:

(For Standard Lens) Powered focus / zoom

F-number:

(For Standard Lens) 1.70 – 2.30

Focal Length:

(For Standard Lens) 24.0 mm – 38.2 mm

Zoom Ratio:

(For Standard Lens) Optical zoom 1.0 – 1.6x

Lens Shift:

(For Standard Lens)

- Vertical: ± 67 degrees
- Horizontal: ± 30 degrees

Projector Details:

Display Performance:

- NTSC: 480 line
- PAL: 576 line
(depends on observation of the multi-burst pattern)

Input Signal:

- NTSC/NTSC4.43/PAL/M-PAL/N-AL/PAL60/SECAM/480i/576i/480p/576p/720p/1080i/1080p
- Pixelworks®: Video Chip 3D Y/C separation, noise reduction motion compensated Interlace-Progressive conversion (2 - 2, 3 - 2 film detection)

Interfaces:

- HDBaseT x 1
- DVI-D x 1
- HDMI x 1
- Computer: D-sub 15 pin x 1
- Component Video: BNC x 1
- Audio-in: Mini stereo x 3
- Audio Out x 1
- Network: RJ-45 x 1, 100 Mbps Serial: RS-232c
- Hardwire remote jack x 1
- Monitor Out: D-sub 15 pin x 1

Fan Noise:

- Normal mode: 39 dB
- ECO mode: 31 dB

Projector Dimensions:

Including feet:

With standard lens: 20.67 x 18.58 x 7.44 (W x D x H)

Excluding feet and lens:

20.67 x 16.73 x 7.28 (W x D x H)

Remote Control:

Features:

Power, source search selection, computer, video, A/V Mute, freeze, user ID, auto, aspect, color mode, number, page up and down, E-zoom, volume, help, menu, enter, esc and pointer functions

Operating Distance:

49 ft

Operating Angle:

Right / Left:

- Front: ± 60 degrees
- Rear: ± 30 degrees

Upper / Lower:

- Front: ±20 degrees
- Rear: +10 to +50 degrees

Power:

Power Supply Voltage:
100 – 240 V ±10%, 50/60 Hz AC

- Power Consumption:**
- Normal mode:601 W
 - ECO mode: 498 W
 - Communication on: 2.0 W standby
 - Communication off: 0.5 W standby

Accessories



Air Filters



Cables



Connectivity



Control Systems



Lamp

Support

Need Support?

Get the latest drivers, FAQs, manuals and more for your Epson product.

Recommended Links:

- Drivers & Downloads
- FAQs
- Manuals and Warranty
- Registration
- Contact Support

Notes:

[†] 4K Enhancement Technology shifts each pixel diagonally by 0.5 pixels to double the resolution and surpass Full HD image quality.

* Color brightness (color light output) measured in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions.

¹ Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118.

² Includes one Mobile High-Definition Link (MHL) HDMI port

IMPORTANT SAFETY INFORMATION ABOUT USAGE ENVIRONMENTS FOR MOUNTED PROJECTORS ►

© 2021 Epson America, Inc.