

EX3280 3LCD XGA Projector



Projectors

Business

Own the Room.

Amazing brightness — 3,600 lumens of color and white brightness¹ ideal for displaying large-group presentations, spreadsheets and videos, even in well-lit rooms

Crisp image quality — XGA resolution delivers crisp text and images; perfect for displaying presentations, video and more

True 3-Chip 3LCD technology — displays 100% of the RGB color signal for every frame, providing outstanding color accuracy while maintaining excellent color brightness, without any distracting “rainbowing” or “color brightness” issues seen with other projection technologies

Versatile connectivity — features an HDMI® port, so you can easily connect streaming devices, including Fire TV, Apple TV®, Roku and Chromecast™²

Easy setup — built-in speaker for easy setup for video and audio right out of the box

Built-in picture skew sensor — automatically analyzes the picture and instantly corrects the vertical keystone to help square the image

Amazing dynamic contrast ratio up to 15,000:1 — provides crisp, rich detail for graphs, images and videos

Award-winning service and support — standard 1-year limited warranty, full-unit replacement, along with free technical phone support for the life of the product

EX3280 3LCD XGA Projector

Specifications

Projection System Epson® 3LCD, 3-chip technology

Projection Method Front/rear/ceiling mount

Driving Method Epson Poly-silicon TFT Active Matrix

Color Brightness¹ Color Light Output: 3,600 lumens

White Brightness¹ White Light Output: 3,600 lumens

Aspect Ratio 4:3

Native Resolution XGA

Resize Support 16:9, 16:10

Lamp Type 210 W UHE

Lamp Life Normal Mode: Up to 6,000

ECO Mode: Up to 12,000 hours

Size (Projected) 30" – 350"

USB Plug 'n Play Projects audio and video, PC and Mac® compatible

Contrast Ratio Up to 15,000:1

Color Reproduction Up to 1.07 billion colors

Projection Lens

Type Manual focus

F-Number 1.44

Focal Length 16.7 mm

Zoom Ratio 1.0 – 1.35 (Digital Zoom)

Throw Ratio Range 1.44 – 1.95

Keystone Correction Manual Vertical: ± 30 degrees

Keystone Correction Manual Horizontal: ± 30 degrees

Other

Display Performance NTSC: 480 lines PAL: 576 lines
(Depends on observation of the multi-burst pattern)

Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/SECAM

Computer Compatibility PC, Mac

Speaker 2 W mono

Media Format 4:3

Operating Temperature 41 ° to 104 °F (5 ° to 40 °C)

Power Supply Voltage 100 – 240 V AC +/- 10%, 50/60 Hz

Power Consumption

Normal Mode: 345 W

ECO Mode: 235 W (lamp on)

Energy Saving: 0.3 W

Fan Noise

Normal Mode: 37 dB

Quiet Mode: 28 dB

Interfaces

1x HDMI

1x D-sub 15-pin

1X USB connector Type-B: USB Plug 'n Play



Dimensions (W x D x H)

Including Feet 11.9" x 9.3" x 3.2"

Excluding Feet 11.9" x 9.2" x 3.0"

Weight 5.2 lb

Remote Control

Features Front and rear directional

Operating Angle

Right/left: ± 30 degrees

Upper/lower: ± 15 degrees

Operating Distance 19.7 ft (6 m)

Eco Features

RoHS compliant

Recyclable product⁴

Epson America, Inc. is a SmartWay® Transport Partner⁵

Support

Epson ConnectionSM Pre-sales support: U.S. and Canada
800-463-7766

Internet website: www.epson.com

Service Programs 1-year projector limited warranty, Epson Extra CareSM Road Service program, PrivateLine® dedicated toll-free support and 90-day limited lamp warranty

What's in the Box

EX3280 projector, power cable, projector remote control, batteries, Quick Start Guide

Ordering Information

EX3280 Projector	V11H975020
Genuine Epson Lamp (ELPLP97)	V13H010L97
Replacement Air Filter (ELPAF32)	V13H134A32
Projector Ceiling Mount (ELPMBPJG)	V12H808001
Soft Carrying Case (ELPKS69)	V12H001K69
Duet™ Screen	ELPSC80
ES1000 Screen	V12H002S4Y
ES3000 Screen	V12H002S3Y