

Home Cinema LS11000 4K PRO-UHD®¹ Laser Projector

3-Chip 3LCD Laser Projector
with HDR10+²

Projectors

4K PRO-UHD¹



Projection Perfected.

4K PRO-UHD®¹ — Advanced pixel-shifting technology works in parallel with three individual high-definition LCD chips without sacrificing picture brightness

Precision Shift Glass Plate Technology — Unique, digitally controlled Precision Shift Glass Plate precisely refracts pixel light to display a 3840 x 2160, 8.29-million-pixel image for an exceptionally sharp and clear picture

Epson® ZX Picture Processor — Our most advanced video processing technology to date, the proprietary 36-bit Epson ZX Picture Processor handles real-time color, contrast, HDR², frame interpolation and resolution enhancement to faithfully reproduce the source material the way it was intended to be shown

Laser Array Light Source — True multi-array laser diodes are the optimum light source to power the unique 3-chip 3LCD projector engine for incredible picture brightness, black contrast and color accuracy

High Picture Brightness — Impressive 2,500 lumens of color and 2,500 lumens of white brightness³ for an exceptional picture in virtually any theater environment—even in rooms with some ambient light

True 3-Chip 3LCD Projector Engine — Advanced 3LCD technology uses three individual LCD chips to continuously display 100% of the RGB color signal for every frame; this allows for outstanding color gamut while maintaining excellent brightness without any rainbowing or color brightness issues seen with other projection technologies

Impressive HDR² — Full 10-bit HDR² color processing accepting 100% of the HDR source information to faithfully reproduce HDR, HDR10+ and HLG (Hybrid Log Gamma) content for an exceptional visual performance; real-time HDR curve adjustment allows for 16 steps of control to fine-tune the HDR performance regardless of the content

120 Hz Refresh Rate — Refresh rates up to 120 Hz allow for smoother motion for supported content while providing the option for impressive frame interpolation for content below 120 Hz



¹ 4K Resolution Enhancement Technology shifts each pixel to produce an image on screen, up to the stated specification.

Home Cinema LS11000 4K PRO-UHD¹ Laser Projector

3-Chip 3LCD Laser Projector with HDR10+²

Projectors

4K PRO-UHD¹

Specifications

Projection System Epson 3LCD
Chip Design (Architecture) 3-Chip
Light Source True Laser Diode Array
Projection Method Front, Front-Ceiling, Rear, Rear-Ceiling
Product Color White
Driving Method Poly-silicon TFT Active Matrix, 0.74" wide panel, 12-bit
Output Resolution 4K PRO-UHD¹ 3840 x 2160 (dual-axis: 1920 x 1080)
Maximum Input Resolution 4096 x 2160
Maximum Refresh Rate 120 Hz
Supported Resolutions 4K 2160p, 2K Full HD 1080p/i, HD 720p, 576p/i, 480p/i
Native Aspect Ratio 16:9 widescreen
Resize Aspect Ratio Support 1.9:1 (4096 x 2160), 21:9 (2560 x 1080), 4:3 (1600 x 1200), 9:6 (720 x 480), 5:4 (720 x 576); compatible with Normal, Full or Zoom Mode
Color Brightness³ Color Light Output: 2,500 lumens
White Brightness³ White Light Output: 2,500 lumens
Contrast Ratio Up to and over 1,200,000:1, Auto Iris on
White Balance 14-point temperature adjustment
Color Reproduction Full-color (up to 1.07 billion colors)
Size (Projected Distance) 50" to 300" (at 58" to 62.4")
Keystone Correction Vertical/Horizontal: ± 30 degrees
HDR² Color Processing Full 10-bit
Epson ZX Picture Processor Full 12-bit
Light Source Life⁵
 Normal Mode: Up to 20,000 hours
 Medium Mode: Up to 20,000 hours
 Eco Mode: Up to 20,000 hours

Projection Lens

Epson VRX Lens 15-element precision glass structure (AGS)
Type Powered focus/optical zoom/lens position
F-number 2.0 – 3.0
Focal Length 22.5 – 46.7 mm
Zoom Ratio 1 – 2.1
Throw Ratio Range 1.35 – 2.84
Lens Shift
 Vertical: -96.3% to +96.3% (H center, powered)
 Horizontal: -47.1% to +47.1% (V center, powered)
Lens Cover Powered, slide lens shutter

Interfaces

2x HDMI[®] 2.1 (HDCP 2.3); one supporting eARC/ARC
 1x USB Type-A (for optical HDMI cable 300 mA maximum power supply only)
 1x USB Type-A 5 V, 2.0 A for power and firmware
 1x Mini USB (service only)
 1x LAN RJ45
 1x RS-232C
 1x Trigger out (On, Off) 12 V DC, 200 mA maximum

Other Features

Dynamic Range Support HDR10², HDR10+², HLG
HDR² Adjustment 16 steps, real-time
Color Modes Dynamic, Vivid, Bright Cinema, Cinema, Natural
Aspect Adjustment Yes (Auto/Full/Zoom)
Frame Interpolation Input up to 4K at 60 Hz, Output up to 4K at 120 Hz
eARC Audio Compatibility LPCM, Dolby[®] Digital AC-3, Dolby Digital Plus, Dolby TrueHD, Dolby Atmos, DTS, DTS-HD, DTS-HD High-Resolution Audio, Master Audio, DTS:X, AAC
Computer Compatibility PC, Mac[®]
ARC Audio Compatibility LPCM, Dolby Digital (AC-3), DTS, AAC
Operating Temperature 41° to 95° F (5° to 35° C)
Power Supply Voltage 100 – 240 VAC ± 10%, 50/60 Hz
Power Consumption
 Normal Mode: 311 W
 Medium Mode: 243 W
 Eco Mode: 204 W
Fan Noise 22 – 30 dB
Security Kensington[®] security lock port
Parental Controls Power Button Lock hinders projector from being turned on without parental supervision

Dimensions (W x D x H)

Projector, including feet (excluding cable cover)
 20.5" x 17.6" x 7.6"
 Weight: 28.0 lb
Packaging
 27.6" x 21.7" x 10.6"
 Weight: 35.7 lb



Remote Control

Features Front and rear directional
Operating Distance 32 ft (10 m)
Operating Angle
 Front Right/Left: ± 30 degrees
 Upper/Lower: ± 30 degrees
 Rear Right/Left: ± 30 degrees
 Upper/Lower: 0 + 60 degrees

Support

Epson ConnectionSM
 Pre-sales support: U.S.: 800-463-7766, Canada: 800-807-7766
 Website: U.S.: www.epson.com, Canada: www.epson.ca
Service Programs 3-year projector limited warranty, Extra CareSM Home Service program, PrivateLine[®] dedicated toll-free support (U.S. and Canada only)

What's in the Box

Home Cinema LS11000 projector, power cord, remote control with (2) AA batteries, Quick Setup Guide

Eco Features

RoHS compliant
 Recyclable product⁶
 Epson America, Inc. is a SmartWay[®] Transport Partner⁷

Ordering Information

Home Cinema LS11000 V11HA48020
 Replacement Air Filter ELPAF62 V13H134AB0

YCbCr									
Resolution	Refresh Rate (Hz)	4:2:0			4:2:2			4:4:4	
		8	10	12	8	10	12	8	10
3840 x 2160	30	Signal does not exist			SDR	HDR*	HDR*	SDR	HDR*
3840 x 2160	60	SDR	HDR*	HDR*	SDR	HDR*	HDR*	SDR	HDR*
3840 x 2160	120	SDR	SDR	-	SDR	HDR*	HDR*	SDR	-