

PowerLite L400U WUXGA 3LCD Laser Projector

Contact Us 800.463.7766

Mon-Fri 7am-4pm PT



Bright, compact WUXGA laser projector with 4,500 lumens.

The compact, affordable PowerLite L400U laser projector delivers powerful performance for education and business applications. Get bright, vivid images with 4,500 lumens color/white brightness¹. This robust projector also offers WUXGA resolution and Full HD support. Featuring breakthrough laser technology, it delivers a laser light source of up to 20,000 hours². And, it offers virtually maintenance-free with no lamps. Plus, it features a Dynamic contrast ratio up to 2,500,000:1. It also features advanced installation features and enterprise-level wireless security support (module sold separately).

Model: V11H907020

OUR PRICE :

\$2,499.00



[Write a review](#)

Overview



Bright, vivid color
4,500 lumens color/white
brightness¹.

Full HD, widescreen
images up to 500"
WUXGA resolution (1920 x 1200);
Full HD 1080p support

Breakthrough laser
technology
features a laser light source of up
to 20,000 hours²; plus, Instant
ON/OFF

Virtually maintenance-
free operation
no lamps

Extraordinary sharpness
and detail
up to 2,500,000:1 Dynamic
contrast ratio

Optional wireless
networking with
enterprise-level security
plus wireless content sharing with
Epson iProjection™³; wireless
module sold separately

- **Versatile connectivity** — 2 ports HDMI®, port VGA, port RJ-45, port mini-stéréo et plus
- **Advanced installation features** — 360-degree flexibility and geometric correction tools such as horizontal and vertical keystone, arc correction, Quick Corner® and more
- **Constant Brightness Mode**⁴ — fine-tune the brightness setting to help maximize run time
- **Remote management and control tools** — compatible with Crestron®, AMX®, PJLink and more; offers easy access and maintenance

Eco Features

- RoHS compliant
- Recyclable product⁵
- Epson America, Inc. is a SmartWay™ Transport Partner⁶

Better Products for a Better Future™

For more information on Epson's environmental programs, go to www.epson.com/environment

IMPORTANT SAFETY INFORMATION ABOUT USAGE ENVIRONMENTS FOR MOUNTED PROJECTORS ►

What's In The Box:

- PowerLite L400U Projector
- Power cord
- Computer cable (VGA)
- Remote control and batteries
- Quick setup poster

Specifications

Specifications Projector:

Projection System:

RGB Liquid Crystal Shutter Projection System

Projection Method:

Front, Front/Ceiling, Rear, Rear/Ceiling

LCD Screen:

0.67" (D10 with C²Fine™)

Driving Method:

Poly-silicon TFT Active Matrix

Pixel Number:

2,304,000 pixels (1920 x 1200) x 3

Color Brightness - Color Light Output:

4,500 lumens¹

White Brightness - White Light Output:

4,500 lumens¹

Aspect Ratio:

16:10

Resolution:

1920 x 1200 (WUXGA)

Throw Ratio Range:

1.35–2.20

Size - projected distance:

80" screen: 2.33–3.78 m

Keystone Correction:

Vertical: ±30 degrees; Horizontal: ±30 degrees

Contrast Ratio:

Up to 2,500,000:1

Color Processing:

10 bit

Color Reproduction:

Up to 1.07 billion colors

Light Source Life:

Normal: 20,000 hours; Quiet: 20,000 hours; Extended: 30,000 hours

Illumination Technology:

Laser Diode

Effective Scanning Frequency Range:

Pixel Clock:

Analog: 13.5–162 MHz (up to UXGA 60 Hz)

Digital: 13.5–162 MHz (up to UXGA 60 Hz)

Horizontal:

Analog: 15–92 kHz

Digital: 15–75 kHz

Vertical:

Analog: 50–85 Hz

Digital: 24/30/50/60 Hz

Projection Lens:

Type:

Optical Zoom (Manual)/Focus (Manual)

F-number:

1.5–1.7

Screen Size:

Zoom: Wide: 50"–500" [1.44–14.76 m]; Zoom: Tele: 50"–500" [2.35–23.84 m]

Focal Length:

20.0–31.8 mm

Zoom Ratio:

1–1.6

Lens Cover:

Lens cap (without string)

Projector Details:

Interfaces:

- 2x HDMI (1x MHL)
- Analog: D-sub 15 pin
- 1x Control I/O: RS-232C D-sub 9 pin
- USB-I/O: Type A 1x; Type B 1x
- Wired LAN RJ45
- Wireless LAN Optional Accessory
- Audio in (stereo): 2x
- Audio out (stereo): 1x

Fan Noise:

38 dB (Normal Mode), 28 dB (ECO Mode)

Projector Dimensions:

Including feet:

17.32" x 11.97" x 5.35" (W x D x H)

Excluding feet:

17.32" x 11.97" x 4.73" (W x D x H)

Weight - with standard lens:

Approx. 17.1 lb/7.8 kg

Remote Control:

Operating Distance:

8 m

Operating Angle:

- Front: Right/Left: ± 60 degrees; Upper/Lower: +30 to -20 degrees
- Rear: Right/Left: ± 30 degrees; Upper/Lower: +50 to +10 degrees

Power:

Power Supply Voltage:

100 – 240 V $\pm 10\%$, 50/60 Hz AC

Power Consumption:

Normal: 324 W; Quiet: 245 W; Networked Standby 2.0 W; Energy Saving: 0.3 W

© 2020 Epson America, Inc.