

XGA Business Projector For Presentation | MX604

High Resolution & High Brightness Projector for Quality and Reliable Daily Presentation For Meeting Room

- 3600 ANSI Lumen High brightness and 20,000:1 High Contrast
- Exclusive Infographic Mode Showcases Text and Graphic in Detail
- SmartEco Mode Saves Lamp Power Up To 70%

Contact Us



MX604	Overview	Specifications	Q&A	Downloads	Contact Us
		Throw Ratio	1.96~2.15		
		Zoom Ratio	1.1X		
		Keystone Correction	1D, Vertical +/- 30 degrees		
		Projection Size	30"~300"		
		Projection Offset**	110%		
Display					
		Projection System	DLP Single 0.55" XGA		
		DMD type	DC3		
		Resolution	1024 x 768 pixels, 4:3		
		Brightness	3,600 Lumens		
		Display Color	1.07 Billion Colors		
		Aspect Ratio	Native 4:3 (5 aspect ratio selectable)		
		Light Source	Lamp, 200W		
		Contrast Ratio	20,000:1		
		Light Source life*	5000/10000/10000/15000 hrs (Normal/Eco/SmartEco/Lamp save mode)		
Audio					
		Built-in Speaker	2W		
Feature					
		Security	Kensington Lock, Security Bar		
Connectivity					
		I/O Port	HDMI x 2/MHL x 1 Computer In (D-sub 15pin, Female)(Share with component) x 1 Monitor out (D-sub 15pin,Female) x 1 Composite Video In (RCA) x 1 S-Video in (Mini Din 4 pin) x 1 Audio in(mini jack) x 1 Audio out (mini jack) x 1 RS232 In x 1 USB TypeA (1.5A power) x 1 USB (Type Mini B) x 1 IR Receiver x2 (Front+Top)		
Compatibility					
		Resolution Support	VGA(640 x 480) to WUXGA(1920 x 1200)		
		Horizontal Frequency	15K - 102KHz		
		Vertical Scan Rate	23-120Hz		

MX604	Overview	Specifications	Q&A	Downloads	Contact Us
-------	----------	----------------	-----	-----------	------------

Power

Standby Power Consumption	Standby <0.5W
Power Consumption (Max/Normal/Eco)	Max 280W. Normal 260W. Eco 210W

Dimension and Weight

Product Dimensions (WxHxD)	296x120x221 mm
Product Weight	2.3Kg

Operation Condition

Operating Temperature	0~40℃
Noise Level	33/29dBA

Accessories

Standard	Remote Control w/ Battery RCX013 White x1 Power Cord (by region) x 1 User Manual CD x 1 Quick Start Guide x 1 Warranty Card (by region) x 1 VGA (D-sub 15pin) Cable x 1 Spare Lamp Kit: 5J.JGP05.001
Optional	3D Glasses P/N: 5J.J9H25.002 Wireless Dongle - QCast: 5J.JCK28.X01 Wireless Dongle - QCast Mirror* : 5A.JH328.10X Ceiling mount: 5J.JAM10.001

OSD

On Screen Display Language	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Persian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Vietnamese (30 Languages)
----------------------------	--

LS2LT1

Lens	F=2.56~2.68, f=22~24.1
------	------------------------

InstaShow Host

Power Supply	AC 100 to 240 V, 50/60 Hz
--------------	---------------------------