



First DLP 4K UHD

Home Cinema Projector



4K UHD Resolution
 8.3 Million Pixels
 4K Upscaling from 1080p
 THX 4K Certified Display
 Rec. 709 Colour Fidelity
 CinemaMasterVideoEnhancer
 1.5x Zoom, H/V Lens Shift









Home Cinema Projector











OPTIONAL ACCESSORY




Ceiling Mount: 5J.JCY10.001

Specification

Model	W11000
Projection System	DLP 4K UHD
Resolution	3840 × 2160 with XPR technology
Display Pixels	8.3 million
Brightness	2200 AL
FOFO Contrast Ratio	50,000:1 with Dynamic Iris
Display Colour	1.07 Billion Colours
Lens	f=2.05 f=20.5~30.4
Aspect Ratio	16:9
Throw Ratio	1.37 - 2.06(100"@3m)
Image Size (Clear Focus/Maximum)	95"~180"/300"
Zoom Ratio	1.5:1
Lamp Type	PHILIPS 240W E22.7
Lamp Mode (Normal/Eco/SmartEco)*	3000 / 4000 / 6000 hours
Lens Shift	Vertical: ± 65% / Horizontal: ± 27%
Resolution Support	VGA(640×480) to 4K2K_RB(4096×2160) *RB = Reduced Blanking
Horizontal Frequency Vertical Scan Rate	15 - 102KHz 23 - 120Hz
Colour Wheel Segment	6-Segment (RGBRGB)
Colour Wheel Speed	6x (50Hz). 4x (60Hz)
·	HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Compatibility	2560×1200, 3840×2160, 4096×2160
	Video Compatibility: NTSC, PAL, SECAM
Vertical Scan Rate	23 - I20Hz
Interface	PC (D-Sub):
Dimensions (L x W x H)	470.7 × 224.9 × 564.7 mm
Weight	14.8kg
Power Supply	AC100 to 240 V, 50 to 60 Hz
Power Consumption	Normal 353W, Eco 290W, Network Standby <6W Standby <0.5W
Audible Noise	26/23 dBA (Normal/Economic mode)
Languages	English/ Spanish/ French (28 Languages)
Picture Mode	** ISF Disabled: Bright / Vivid / Cinema/THX/ Silence/ User I / User 2 *** ISF Disabled: Bright / Vivid / Cinema/THX/ Silence/ User I / User 2 / ISF Night / ISF Day
Accessories (Standard)	Lens Cover, Remote Control with Battery, Power Cord (by region), User Manual CD, Quick Start Guide, Warranty Card
Accessories (Optional)	Spare Lamp Kit, Ceiling Mount, Anamorphic lens
Environmental Notice	Lamp in this product contains mercury. To dispose of the product or used lamps, consult your local environment authorities for regulations or see www.lamprecycle.org .

^{*} Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice. ** Default picture mode is THX. *** When ISF is enable, default picture mode is ISF Night.



Lens Optimized for 4K Images

- 4K lens featuring 14-piece lens in six grouping structure
- 6-piece extra low dispersion coating glass lens

 $\label{lem:continuous} Greater\ Light\ Penetration\ to\ provide\ 4K\ details \\ with\ Best\ Color,\ Clarity\ \&\ Sharpness$













Dealer's Stamp

HCC/AIM Free Call (AU) 1800 008899 homecinemacentral.com.au



© 2016 BenQ Corp. Specification may very by region, please visit your local stores for details. Actual product's features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively. Doc:WI 1000_DS_EN_201610