

Ultra Short-Throw Projectors

PJ WX4152
PJ WX4152N
PJ WX4152NI

RICOH
imagine. change.



Tiny throw, small size, big impact

New to the ultra-short throw category, these three compact projectors provide exceptional quality, choice and convenience. For schools, universities, colleges and laboratories, almost any space previously considered restricted can now become a productive venue for bright and engaging presentations. These portable, lightweight models are perfect for event signage too, enabling projection at 48" from a distance of only 11.7cm from the chosen surface.

- Short projection distance from 11.7cm
- MPEG4 compatible to show video
- 4in1, able to connect with 4 different computers and project in 1 screen
- Unique and modern design
- Light in weight and small footprint.



Small spaces have big possibilities

Connectivity and interactivity.

This outstanding range has three strong projectors, each delivering exceptional functionality, and between them offering a spectrum of solutions to suit any customer's needs. PJ WX4152N offers the possibility of network connection (wired and WiFi/Wireless). PJ WX4152NI has the same functionality complemented with interactive pen which allows the user to write.



Compatible and multiple.

MPEG4 compatibility allows you to use video, further enhancing the presentation possibilities. The 4in1 function enables you to connect with four PCs simultaneously or MacBooks. A convenient Quick Projection feature is available via software compatible with N and NI models. The application allows the projectors to show images such as computer screens, still images, and movies via a network.



Start fast. Finish fast. Save time.

You can quickly start the projection – the power is automatically on, no need to press any button. The start screen comes up just 3 seconds after the projector is connected to the electricity source, so your presentation is up and running right away and you attract the audience's attention immediately. There's a quick shutdown routine too, with no need to wait for cooling.

No ceiling, no problem.

In premises where the ceiling is too high or simply unsuitable for hanging a conventional projector, these location-friendly models can simply be placed right under the wall, freeing up space elsewhere in the room. They are also compact enough to be easily and discreetly concealed when necessary, simplifying the space organization.

PJ WX4152/ PJ WX4152N/ PJ WX4152NI

MAIN SPECIFICATIONS

GENERAL

| | |
|---|--|
| Projection system: | Single chip DLP |
| Resolution: | 1,280 x 800 pixels |
| Panel: | Panel size: 0.65 inch |
| Brightness: | 3,500 lumen |
| Colour reproducibility: | 1,073,000,000 colours |
| Contrast ratio: | 13,000:1 |
| Projection screen size: | 48" to 80" |
| Projection distance: | 18.8 to 31.7 cm (from rear of unit to projection surface) |
| Lamp: | High-pressure mercury lamp: standard: 250 W, Eco mode: 150 W |
| Lamp life: | Standard: 3,500 hours Eco mode: 5,000 hours |
| RGB compatible signals : | VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, UXGA |
| Input signals: | NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-N, PAL-60, 50 Hz (mono), 60 Hz (mono) |
| Zoom ratio: | 80% - 100% |
| Magnify: | 100%, 125%, 150%, 175%, 200% |
| Zoom: | Digital |
| Focus: | Manual |
| Connection terminal: | Mini D-SUB15pin x 1 (Computer IN) , RCA_1pin x 1 (Video), Mini Jack x 1 (Audio1 IN/OUT) , USB-TYPE-minB x1, HDMI x 1 |
| USB (PJ WX4152N, PJ WX4152NI): | Type-A x 1, USB 2.0 High-Speed |
| Wired LAN (PJ WX4152N, PJ WX4152NI): | RJ-45 x 1 (10BASE-T/100BASE-TX/1000BASE-T) |
| Wireless LAN (PJ WX4152N, PJ WX4152NI): | LAN IEEE 802.11b/g/n compliant |
| Wireless LAN (PJ WX4152N, PJ WX4152NI): | Network authentication: None, Open system, Common key, WPA-PSK, WPA2-PSK, WPA-EAP, WPA2-EAP Network encryption: None, WEP, TKIP, CCMP(AES) |
| Primary features: | Mute (Blank), Freeze, Re-size (Magnify), Auto keystone, Password protection, Blackboard mode, Key lock, User logo, Eco mode, Carbon meter, Closed captioning, Color Universal Design, 3D Ready, Image Eco, Sound mode, Simple DICOM, Presentation Timer, Power timer |
| Built-in speaker: | 2 W mono |
| Network features (PJ WX4152N, PJ WX4152NI): | Network projection, Multi-screen (1 PC to 4 projectors), 4 in 1 projection (discussion mode), Projector management, PJ Link, PENTAX-Ricoh camera projection (USB), Web Image Monitor, DLNA support, Crestron, AMX, Wi-fi, UPnP, Remote Whiteboard Sharing (PJ WX4152NI), Smart Presenter, Smart Device Connector |
| Dimensions (W x D x H): | 257 x 144 x 221 mm |
| Weight: | 3 kg |
| Power source: | 100 - 240 V, 50/60 Hz |

- g/m²

ECOLOGY

| | |
|------------------------|--|
| Power consumption: | Operating power: 313 W Energy Saver mode: 208 W Stand-by mode: 0.3 W |
| Operating temperature: | 5°C - 35°C |
| Operating humidity: | 30% - 70% |

CONSUMABLES

Replacement lamp Type 11

ACCESSORIES

Set-up guide & safety instructions, RGB cable, Power cable, Remote control with batteries, Carrying bag

SUPPORTED OS

| | |
|--|---|
| Advanced Network Utility : | Windows Vista SP2 or later Windows 7 Windows 8 Windows 8.1 Windows 10 Mac OS X |
| Projection management utility / JPEG conversion utility: | Windows Vista SP2 or later Windows 7 Windows Server 2008 Windows Server 2008R2 Windows 8 Windows 8.1 Windows 10 |
| Interactive drawing software (PJ WX4152NI): | Windows 7 Windows 8 Windows 8.1 Windows 10 |

For availability of models, options and software, please consult your local supplier.

ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2018 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

RICOH
imagine. change.

www.ricoh-europe.com