

VPL-SX630

3,200 lumens XGA Ultra
Short Throw projector



Overview

Bright, high contrast projector with easy installation, environmentally friendly features ideal for mid size rooms, with optional wireless connectivity

Thanks to 3LCD BrightEra™ panel technology by Sony, users can enjoy extremely bright, high contrast, XGA images with excellent colour stability. The projector's powerful 3200 lumens colour light output ensures that presentations are always seen clearly, even when ambient light levels are high. Easy to install with plenty of interfaces for connection with other devices, the VPL-SX630 integrates seamlessly with school or office networks. Adding an optional Wi-Fi module lets users wirelessly share homework, images and graphics from devices like PCs, smartphones and tablets. There's a wide range of smart energy-saving features built in. In addition, extended lamp replacement time up to 8,000 hours allows for synchronised filter and lamp maintenance, reducing the product's downtime and minimising costs.

3LCD Color Light Output colour reproduction and high brightness

3200 lumen brightness with native XGA (1024 x 768) 4:3 screen resolution.

Long-lasting lamp

8000 hours in Low mode.

Wireless presentation with tablet

The wireless presentation capability makes it easy to present files from your tablet device or smart phone.

Installation friendly

Using lens shift function, the position of the projected image can be moved vertically by -3.1% to +3.1% and horizontally by -2.3% to +2.3% and x 1.03 optical zoom for easy adjustment.

Features

Extremely bright, clear images with maximum 3200 lumens colour light output

The projector's high light output ensures that presentations are seen clearly in any classroom or meeting room. There's a choice of three brightness modes to suit any environment, from bright daylight to darkened rooms.

XGA resolution for detail-packed presentations

XGA (1024 x 768) 4:3 screen resolution gives lots of crisp, fine detail: perfect for making presentations direct from a laptop or PC.

3LCD BrightEra™ technology

The projector's efficient 3LCD panel system is enhanced by advanced BrightEra™ technology by Sony. You'll see the difference with impressively bright, high resolution images and increased panel reliability.

Up to 8000 hours long-lasting lamp for reduced maintenance and down time

Teach for longer without interruption, with reduced maintenance that contributes directly to lower lifetime ownership costs. Filter cleaning cycles are synchronised

with lamp replacement, cutting scheduled maintenance visits even further.

Advanced energy-saving features

Advanced lamp technology enables robust energy-saving features. For example, greater brightness control in Auto Light Dimming mode saves considerable energy when the projector is left on without being used. During projection, Auto Picture Mode automatically adjusts light output to suit the projected scene. When you need to mute the picture temporarily, light output can be completely deactivated to minimise energy consumption.

Network presentation (LAN/Wireless LAN)

When the projector is installed on a LAN/Wireless LAN, presentations can be projected from any PC and Mac on the network. A tablet or smart phone can be connected at the same time. The wireless presentation capability makes it easy to present files from your tablet device or smart phone. You can project jpg, pdf and other supporting formats. Up to four users can project PC/Mac images simultaneously, while up to eight users can connect to one projector. For Windows/Mac, an application "Projector Station for Network Presentation" is provided. For tablet/smartphone, an application is provided by Pixelworks, downloaded from the web. For details, please visit the following website:
<http://PWPresenter.pixelworks.com>

Remote control for iOS device

Projector Remote is simple remote control app for Sony's projectors. Networked projectors can be controlled by this remote app. Remote Control allows you to operate the projector with simple and easy-to-read buttons.

Networked control

Projector functions and status can also be managed and monitored remotely from any user's PC on the network. For Windows, an application "Projector Station for Network Control" is provided.

USB Media viewer

Insert a USB drive to effortlessly display photos, images and graphics with no PC needed.

USB display

The projector allows you to display pictures and audio* with one USB cable. You do not need to install any driver for this function. It is a convenient way to connect to the projector when you want to connect easily.

* There is a time lag in video and audio. When not in simple use, it is recommended to use Line-in or HDMI-in.

Clear, rich audio from built-in speaker

There's no need to add an extra audio system: enjoy rich, room-filling sound from the powerful 16W speaker.

Easy to install

Adjustable optical zoom and lens shift simplify speedy, fuss-free installation in any classroom. Generous connections simplify hook-ups with PCs, DVD players, microphones and other AV devices.

Specifications	Display System	
	Display System	3 LCD system
	Display device	
	Size of effective	0.63" (16.0 mm) x 3 BrightEra

display area	LCD Panel, Aspect ratio: 4:3
--------------	------------------------------

Number of pixels	2,359,296 (1024 x 768 x 3) pixels
------------------	-----------------------------------

Projection lens

Focus	Manual
-------	--------

Zoom - Powered/Manual	Manual
--------------------------	--------

Zoom - Ratio	Approx. x 1.03
--------------	----------------

Throw Ratio	0.27:1 to 0.27:1
-------------	------------------

Lens shift - Powered/Manual	Manual
--------------------------------	--------

Lens shift - Range Vertical	+/- 3.1%
--------------------------------	----------

Lens shift - Range Horizontal	+/- 2.3%
----------------------------------	----------

Light source

Type	Ultra high pressure mercury lamp
------	----------------------------------

Wattage	225 W type
---------	------------

Recommended lamp replacement time *1

Lamp mode: High	3000 H
-----------------	--------

Lamp mode:	5000 H
------------	--------

Standard

Lamp mode: Low	8000 H
----------------	--------

Filter cleaning / replacement cycle (Max.) *1

Filter cleaning / replacement cycle (Max.)	Same time as the lamp replacement is recommended
--	--

Screen size

Screen size	70" to 115" (1.78 m to 2.92 m) (measured diagonally)
-------------	--

Light output

Lamp mode: High	3200 lm
-----------------	---------

Lamp mode: Standard	2600 lm
---------------------	---------

Lamp mode: Low	2100 lm
----------------	---------

Color light output

Lamp mode: High	3200 lm
-----------------	---------

Lamp mode: Standard	2600 lm
---------------------	---------

Lamp mode: Low	2100 lm
----------------	---------

Contrast ratio (full white / full black) *2

Contrast ratio (full white / full black) *2	3000:1
---	--------

Speaker

Speaker	16 W x 1 (monaural)
---------	---------------------

Displayable scanning frequency

Horizontal	15 kHz to 92 kHz
Vertical	48 Hz to 92 Hz

Display resolution

Computer signal input	Maximum display resolution: UXGA 1600 x 1200 dots*3
Video signal input	NTSC, PAL, SECAM, 480/60i, 576/50i, 480/60p, 576/50p, 720/60p, 720/50p, 1080/60i, 1080/50i, The following items are available for digital signal (HDMI input) only;1080/60p,1080/50p

Color system

Color system	NTSC3.58, PAL, SECAM, NTSC4.43, PAL-M, PAL-N
--------------	--

Keystone correction (Max.)

Vertical	+/- 5 degrees
----------	---------------

OSD language

OSD language	24-languages (English, Dutch, French, Italian, German, Spanish, Portuguese, Turkish, Polish, Russian, Swedish, Norwegian, Japanese, Simplified Chinese, Traditional Chinese, Korean, Thai, Vietnamese, Arabic, Farci, Finnish, Indonesian, Hungarian, Greek)
--------------	--

INPUT OUTPUT (Computer/Video/Control)

INPUT A	RGB / Y PB PR input connector: Mini D-sub 15-pin (female) Audio input connector: Stereo mini jack
INPUT B	RGB input connector: Mini D-sub 15-pin (female) Audio input connector: Stereo mini jack
INPUT C	HDMI input connector: HDMI 19-pin, HDCP support
S VIDEO IN	S Video input connector: Mini DIN 4-pin Audio input connector: Pin

	jack x2 (shared with VIDEO IN)
VIDEO IN	Video input connector: pin jack Audio input connector: Pin jack x2 (shared with S VIDEO IN)
OUTPUT	Monitor output connector*4: Mini D-sub 15-pin (female) Audio output connector*5: Stereo mini jack (variable out)
REMOTE	RS-232C connector: D-sub 9-pin (male)
LAN	RJ-45, 10BASE-T/100BASE-TX
USB	Type-A
USB	Type-B
MICROPHONE IN	Microphone input: Mini jack

Acoustic noise

Lamp mode: Low 28 dB

Operating temperature / Operating humidity

Operating temperature / Operating humidity 0°C to 40°C (32°F to 104°F) / 20% to 80% (no condensation)

Storage temperature / Storage humidity

Storage temperature / Storage humidity	-10°C to +60°C (14°F to +140°F) / 20% to 80% (no condensation)
--	--

Power requirements

Power requirements	AC 100 V to 240 V, 3.2 A to 1.4 A, 50 Hz / 60 Hz
--------------------	--

Power consumption

AC 100 V to 120 V	Lamp mode : High : 318 W
AC 220 V to 240 V	Lamp mode : High : 306 W

Standby mode power consumption

AC 100 V to 120 V	0.5 W (when “Standby mode” is set to “Low”)
AC 220 V to 240 V	0.5 W (when “Standby mode” is set to “Low”)

Power Consumption (Networked Standby Mode)

	5.2 W (LAN) 5.7 W (optional WLAN module)
AC 100 V to 120 V	5.9 W (ALL Terminals and Networks Connected, when "Standby Mode" is set to "Low")

	"Standard")
AC 220 V to 240 V	5.5 W (LAN) 5.9 W (optional WLAN module) 6.2 W (ALL Terminals and Networks Connected, when "Standby Mode" is set to "Standard")

Standby Mode / Networked Standby Mode Activated

Standby Mode / Networked Standby Mode Activated	After about 10 Minutes
---	------------------------

Wireless Network(s) On/Off Switch

Wireless Network(s) On/Off Switch	1) Press the MENU button, then select [Connection/Power] 2) [WLAN Settings] 3) [WLAN Connection] 4) Select On or Off
-----------------------------------	---

Heat dissipation

AC 100 V to 120 V	1085 BTU/h
AC 220 V to 240 V	1044 BTU/h

Dimensions (W x H x D)

Dimensions (W x H

x D) (without protrusions)

Approx. 372 x 168 x 382 mm
(14 21/32 x 5 7/16 x 15 1/32 inches)

Mass

Mass

Approx. 6.0 kg (13 lb)

Supplied accessories

Remote commander

RM-PJ8

Optional Accessories

Replacement lamp

LMP-E220

Wireless LAN module

IFU-WLM3

Notes

*1

This figure is expected maintenance time, not guaranteed time. The actual value depends on the environment and how the projector is used.

*2

The value is average.

*3

Available for VESA Reduced Blanking signal.

*4

From INPUT A and INPUT B.

*5

Works as an audio switcher function. Output from a selected channel; not available in standby.

Environmental notice for customers in the USA

Lamp in this product contains mercury. Disposal of these materials may be regulated due to environmental considerations. For disposal or recycling information, please contact your local authorities or see www.sony.com/mercury for additional information.

Gallery

