

Pro L1060WNL WXGA 3LCD Laser Projector

Contact Us
800-442-1977

Mon-Fri 7am-5pm PT



Premium, compact large-venue laser projector.

The powerful Pro L1060WNL, part of Epson's most compact interchangeable-lens laser projector series, offers 3-chip 3LCD technology and native WXGA resolution for widescreen images, all in a sleek white casing. Delivering extraordinary color brightness, Epson® 3LCD projectors ensure brilliant images. Providing 6,000 lumens of color brightness and 6,000 lumens of white brightness¹, the L1060WNL's laser light source and air filter offer virtually maintenance-free operation up to 20,000 hours². With a high contrast ratio and BT.709 color space, it produces sharp, true-to-life images. And, it offers 11 interchangeable lens options (lens not included).

Some lenses will not support the maximum brightness level of this projector. **VIEW THE PDF ►**

Model: V11H958920

Overview

Ultra bright

6,000 lumens color/white brightness¹ from a compact large-venue laser projector

Exceptional widescreen display

native WXGA resolution for widescreen images; provides up to 1 million pixels on screen

Vibrant, true-to-life images

with Epson 3-chip 3LCD technology

Worry-free operation

solid-state laser light source and air filter provide virtually maintenance-free operation for up to 20,000 hours²

11 optional interchangeable lenses

with powered lens shift and lens memory, including an ultra short-throw lens with zero offset (lens not included)

Lifelike images

high contrast ratio and BT.709 color space for exceptional clarity and detail

- **Dynamic projection capabilities** — advanced built-in Edge Blending, image warping and shape overlay features for a variety of applications; direct playback from USB storage media
- **Simplified installation features** — full 360-degree mounting, wide lens shift, versatile connectivity; inputs including HDBaseT™ and HDMI® (HDCP 2.2)
- **Customized performance** — brightness modes to maximize light source life and provide a consistent brightness level
- **Multi-projector setup software** — free software controls networked projectors and gives access to warping and edge blending
- **Web- or network-based remote management** — control and monitor projector status

Eco Features

- RoHS compliant
- Recyclable product³
- Epson America, Inc. is a SmartWay™ Transport Partner⁴

Better Products for a Better Future™

For more information on Epson's environmental programs, go to www.epson.com/environment

What's In The Box:

- Pro L1060WNL projector
- power cable
- cable cover
- projector remote control with batteries
- Quick Setup Sheet

Specifications



Specifications Projector:

Projection System:

High-aperture Epson® 3LCD, 3-chip technology

Projection Method:

Front/rear/ceiling mount

Driving Method:

Poly-silicon TFT Active Matrix

Resolution on Screen:

WXGA up to 1.0 million pixels

Pixel Number in Device:

1,024,000 pixels (1280 x 800) x 3 chips

Signal Input:

Maximum display resolution 1920 x 1080 (resizing display)

Display resolution 1280 x 800 pixels

Color Brightness - Color Light Output:

6,000 lumens¹

White Brightness - White Light Output:

6,000 lumens¹

Aspect Ratio:

Supports 4:3, 16:9, 16:10

Brightness Uniformity:

85%

Pixel Arrangement:

Cross stripe

Keystone Correction:

Vertical: ±45 degrees; horizontal: ±30 degrees

Contrast Ratio:

2,500,000:1 (Dynamic Contrast: On)

Color Reproduction:

Up to 1.07 billion colors

Light Source Life:

20,000 hours (Normal)²

Illumination Technology:

Laser Phosphor

General:

Operating Temperature:

32 ° to 113 ° F (0 ° to 45 ° C)

Weight:

34.4 lb without lens

Security:

Security cable hole, Kensington lock provision

Projection Lens:

Type:

Powered shift/focus/zoom (ELPLM08 Lens)

F-number:

1.7 – 2.3 (ELPLM08 Lens)

Focal Length:

24.0 mm – 38.2 mm (ELPLM08 Lens)

Zoom Ratio:

Optical zoom 1 – 1.6x (ELPLM08 Lens)

Throw Ratio Range:

1.44 – 2.32 (ELPLM08 Lens)

Lens Shift:

Vertical: ±67 percent; Horizontal: ±30 percent (ELPLM08 Lens)

Projector Details:

Input Signal:

Input Video Signal (HDMI, DVI-D and HDBaseT ports) 480i/480p/576i/576p/720p/1080i/1080p/3840 x 2160/ 4096 x 2160

Interfaces:

- DVI-D x 1
- HDMI (HDCP 2.2) x 1
- HDBaseT x 1
- 5-BNC, VGA x 1
- Audio in: Mini Stereo x 3
- Variable audio out: Mini Stereo x 1
- USB connector Type B x 1: For service only
- USB connector Type A x 1: For wireless LAN, service, content playback
- Monitor out: Mini D-sub 15-pin x 1
- Serial: RS-232c x 1
- Remote Stereo Mini x 1
- Wired LAN: RJ45

Fan Noise:

34 dB (Normal Mode); 32 dB (Medium Mode) 30 dB (Quiet Mode)

Projector Dimensions:

Including feet - with standard lens:

21.5" x 7.4" x 19.1" (545 x 189 x 484 mm)

Remote Control:

Features:

Operating Distance:
98 ft


- Operating Angle:**
- Right/left: Front: ± 60 degrees; Rear: ± 30 degrees
 - Upper/lower: Front: + 30 to - 20 degrees; Rear: +50 to + 10 degrees

Power:

Power Supply Voltage:
100 – 240 V ±10%, 50/60 Hz AC

Power Consumption:
361 W (Normal Mode), 263 W (Extended Mode), 2W (Network Standby), 0.5 W (Energy Saving)


Accessories



Air Filters



Connectivity



Control Systems



Lenses



Mounts

Support

Need Support?

Recommended Links:

- Drivers & Downloads
- FAQs
- Manuals and Warranty

Get the latest drivers, FAQs, manuals and more for
your Epson product.

Registration
Contact Support

Notes:

¹ Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118.

² No required maintenance for the light source and filter up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period.

³ For convenient and reasonable recycling options, visit www.epson.com/recycle

⁴ SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

© 2021 Epson America, Inc.