


KeyFeatures

Free-standing Dual-sided Design | Built-in Quad Core Media Player with
16GB Storage | Pre-installed Standard and Touch Displays | Embedded
LAN, Wi-Fi, and Browser | Internal Scheduler




ProductDescription

With dual 55" screens, the ViewSonic® EP5500D-1 ePoster digital kiosk delivers a dynamic, double-sided signage solution. Great for grabbing attention in busy, high-traffic areas, the EP5500D-1 all-in-one kiosk features a 10-point Full HD touchscreen (CDM5500T) on one side, and a static Full HD screen (CDM5500R) on the other side. 178°/178° wide viewing angles, 450-nit brightness, 1,100:1 contrast ratio, and 10W stereo speakers all combine to deliver engaging content. Each screen is integrated with a powerful Quad-core media player and 16GB of internal memory, allowing each screen to be driven separately with its own content for increased multimedia messaging. You can also add your own media player using the convenient media player cradle located inside the kiosk's lockable security door. Each screen is also protected by a scratch-proof tempered glass faceplate and acrylic overlay for added durability and reliable messaging 24 hours a day, 7 days a week.



55"
DISPLAY



1920 x 1080
RESOLUTION



450 cd/m2
BRIGHTNESS

24/7

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Display Size (in.):	55
Viewable Area (in.):	54.6
Resolution:	1920 x 1080
Light Source:	ELED
Static Contrast Ratio:	1,100:1
Brightness:	450 cd/m2
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	50,000
Response Time (Typical GTG):	12ms
Panel Surface:	Anti-glare, Hard coating (3H)
Panel Type:	IPS
Aspect Ratio:	16:9
Operation Rating:	24/7

Audio:

Internal Speakers:	10W (x2)
--------------------	----------

Connector:

3.5mm Audio In(1), 3.5mm Audio Out(1), DVI-I(1), DVI-I Out(1), DisplayPort(1), DisplayPort Out(1), Ethernet LAN (RJ45)(1), HDMI 1.4 In(2), IR in(1), IR out(1), RS232 In(1), RS232 Out(1), USB 2.0 Type A(2), Micro USB(1), Micro SD Card Slot(1)

Embedded Player:

Media Player Type:	Yes
CPU:	Quad core A9 CPU - RK3188

Touch:

Touch Technology:	Infrared
Touch Points:	10-Point Touch

Power:

Voltage:	100-240 VAC
Consumption (max):	260W
Consumption (typical):	150W
Stand-by:	<1W

Operating Conditions:

Temperature:	41-104° F (5 - 40° C)
Humidity (non-condensing):	10-90%

Mount:

VESA Compatible:	400 x 400 mm
------------------	--------------

Weight (imperial):

Gross (lbs):	315.4
Net (lbs):	293.9

Weight (metric):

Gross (kg):	143.1
Net (kg):	133.3

Dimensions (imperial) (WxHxD):

Packaging (in.):	40.0 x 80.0 x 48.0
Physical (in.):	32.5 x 75.4 x 23.9

Dimensions (metric) (WxHxD):

Packaging (mm):	1016.0 x 2032.0 x 1219.2
Physical (mm):	824.5 x 1915.4 x 606.6

Controls:

On Screen Display:	POWER, MUTE, INPUT, VOL +/-, UP, DOWN, MENU
--------------------	---

General:

Regulations: UL/cUL, FCC, Energy Star 7.0, UL-MX-CoC, Mexico Energy

PACKAGE CONTENTS: STND-052, CDM5500R, CDM5500T, Remote control, User Manual, Quick Start Guide, power cables, RS232 cable, IR sensor cable, RS232 daisy chain cable

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: One-year limited warranty

UPC: 766907002669

Accessories:

NMP-302WX, NMP-302w, NMP520-W, NMP520-WX, NMP580-W, NMP620-P10, NMP620-P10X, SW-071, SW-072, SW-073, SW-074, SW-075, SW-090, SW-091, SW-092, SW-093, SW-094, SW-095, SW-096