

Display:

Display Size (in.):	55
Viewable Area (in.):	54.6
Resolution:	1920 x 1080
Light Source:	ELED
Static Contrast Ratio:	1,100:1
Brightness:	450 cd/m2
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	50,000
Response Time (Typical GTG):	12ms
Panel Surface:	Anti-glare, Hard coating (3H)
Panel Type:	IPS
Aspect Ratio:	16:9
Operation Rating:	24/7

Audio:

Internal Speakers:	10W (x2)
--------------------	----------

Connector:

3.5mm Audio In(1), 3.5mm Audio Out(1), DVI-I(1), DVI-I Out(1), DisplayPort(1), DisplayPort Out(1), Ethernet LAN (RJ45)(1), HDMI 1.4 In(2), IR in(1), IR out(1), RS232 In(1), RS232 Out(1), USB 2.0 Type A(2), Micro USB(1), Micro SD Card Slot(1)

Embedded Player:

Media Player Type:	Yes
CPU:	Quad core A9 CPU - RK3188

Touch:

Touch Technology:	Infrared
Touch Points:	10-Point Touch

Power:

Voltage:	100-240 VAC
Consumption (max):	260W
Consumption (typical):	150W
Stand-by:	<1W

Operating Conditions:

Temperature:	41-104° F (5 - 40° C)
Humidity (non-condensing):	10-90%

Mount:

VESA Compatible:	400 x 400 mm
------------------	--------------

Weight (imperial):

Gross (lbs):	344.1
Net (lbs):	322.6

Weight (metric):

Gross (kg):	156.1
Net (kg):	146.3

Dimensions (imperial) (WxHxD):

Packaging (in.):	40.0 x 80.0 x 48.0
Physical (in.):	32.5 x 75.4 x 23.9

Dimensions (metric) (WxHxD):

Packaging (mm):	1016.0 x 2032.0 x 1219.2
Physical (mm):	824.5 x 1915.4 x 606.6

Controls:

On Screen Display:	POWER, MUTE, INPUT, VOL +/-, UP, DOWN, MENU
--------------------	---

General:

Regulations: UL/cUL, FCC, Energy Star 7.0, UL-MX-CoC, Mexico Energy

PACKAGE CONTENTS: STND-052, CDM5500T x 2, Remote control, User Manual, Quick Start Guide, power cables, RS232 cable, IR sensor cable, RS232 daisy chain cable

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: One-year limited warranty on parts, labor and backlight

UPC: 766907002676

Accessories:

NMP-302WX, NMP-302w, NMP520-W, NMP520-WX, NMP580-W, NMP620-P10, NMP620-P10X, SW-071, SW-072, SW-073, SW-074, SW-075, SW-090, SW-091, SW-092, SW-093, SW-094, SW-095, SW-096