

Key **Features**

Free-standing Dual-sided Design | Built-in Quad Core Media Player with 16GB Storage | Pre-installed Commercial Displays | Embedded LAN, Wi-

Fi, and Browser | Internal Scheduler



Product **Description**

With dual 55" screens, the ViewSonic* EP5500D-4 ePoster digital kiosk delivers a dynamic, double-sided signage solution. Great for grabbing attention in busy, high-traffic areas, the EP5500D-4 all-in-one kiosk features two static Full HD screens (CDM5500R). 178°/178° wide viewing angles, 450-nit brightness, 1,100:1 contrast ratio, and 10W stereo speakers all combine to deliver engaging content. Each screen is integrated with a powerful Quad-core media player and 16GB of internal memory, allowing each screen to be driven separately with its own content for increased multimedia messaging. You can also add your own media player using the convenient media player cradle located inside the kiosk's lockable security door. Each screen is also protected by a scratch-proof tempered glass faceplate and acrylic overlay for added durability and reliable messaging 24 hours a day, 7 days a week.

24/7







call: 888.881.8781Contact Salesemail: salesinfo@viewsonic.comvisit: viewsonic.com

Display:

Display Size (in.): 55

Viewable Area (in.): 54.6

Resolution: 1920 x 1080

Light Source: ELED

Static Contrast Ratio: 1,100:1

Brightness: 450 cd/m2

Viewing Angles: 178° horizontal, 178° vertical

Backlight Life (Hours): 50,000
Response Time (Typical GTG): 12ms

Panel Surface: Anti-glare, Hard coating 3H

Panel Type: IPS
Aspect Ratio: 16:9
Operation Rating: 24/7

Connector:

3.5mm Audio In(1), 3.5mm Audio Out(1), DVI-I(1), DVI-I Out(1), DisplayPort(1), DisplayPort Out(1), Ethernet LAN (RJ45)(1), HDMI 1.4 In(2), IR in(1), IR out(1), USB 2.0 Type A(1), Micro USB(1), Micro SD Card Slot(1)

Embedded Player:

Media Player Type: Yes

CPU: Quad core A9 CPU - RK3188

Power:

Voltage: 100-240 VAC

Consumption (max): 260W

Consumption (typical): 150W

Stand-by: <1W

Operating Conditions:

Temperature: 41-104° F (5 - 40° C)

Humidity (non-condensing): 10-90%

Mount:

VESA Compatible: 400 x 400 mm

Weight (imperial):

Gross (lbs): 286.7 Net (lbs): 265.2

Weight (metric):

Gross (kg): 130.0
Net (kg): 120.3

Dimensions (imperial) (WxHxD):

Packaging (in.): 40.0 x 80.0 x 48.0 Physical (in.): 32.5 x 75.4 x 23.9

Dimensions (metric) (WxHxD):

Packaging (mm): 1016.0 x 2032.0 x 1219.2 Physical (mm): 824.5 x 1915.4 x 606.6

Controls:

On Screen Display: POWER, MUTE, INPUT, VOL -/+, UP, DOWN, MENU

General:

Regulations: UL/cUL, FCC, Energy Star 7.0, UL-MX-CoC, Mexico Energy

PACKAGE CONTENTS: STND-052, CDM5500R x 2, Remote control, User Manual, Quick Start Guide, power cables, RS232 cable, IR sensor cable, RS232 daisy chain cable

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: One-year limited warranty

UPC: 766907002683

Accessories:

NMP-302WX, NMP-302w, NMP520-W, NMP520-WX, NMP580-W, NMP620-P10, NMP620-P10X, SW-071, SW-072, SW-073, SW-074, SW-075, SW-090, SW-091, SW-092, SW-093, SW-094, SW-095, SW-096

Copyright © ViewSonic Corporation 2000-2021. All rights reserved. (10/25/2021 11:40 PM PST)